AKM® Servo Motor

Three-Phase AC Permanent Magnet Servo Motor

Selection Guide



KOLLMORGEN

A REGAL REXNORD BRAND

Kollmorgen: Your Partner, In Motion.

Every solution comes from a real understanding of the challenges facing machine designers and users.

Innovators consistently rate Kollmorgen as one of their best motion systems manufacturing partners. Whether you are looking for classic servo motors, direct-drive servo motors, stepper motors, drives & amplifiers, gearing, actuation, or multi-axis motion controllers, Kollmorgen is one of the few companies in the world that actually designs and manufactures all of these products.

Our customers are leaders in many industries such as Aerospace & Defense, Printing, Packaging & Converting, Food & Beverage Processing, Medical Imaging, In Vitro Diagnostics & Laboratory Automation, Pharmaceutical Manufacturing, Material Forming and Cutting, Oil & Gas, and Robotics. Kollmorgen is also a leader in Warehouse Automation, including complete AGV systems, software, awareness and autonomy.

Our Automation Solutions can be found on Mars and in space, ships and submarines, O&G drilling and metrology, surgical robots and laser eye surgery, even inside artificial hearts. These are just a few applications that demand high-performance and high-quality while satisfying their specific needs.

Because motion matters, it's our focus: Motion can distinctly differentiate a specific machine and deliver a marketplace advantage by increasing its performance and dramatically improving Overall Equipment Effectiveness (OEE).

High-performance motion can make your customer's machine more reliable and energy-efficient, enhance accuracy and improve operator safety. Motion also represents endless possibilities for innovation.

We've always understood this potential, and thus have kept motion at our core and in our Vision, Mission & Values, relentlessly developing products that offer precise control of torque, velocity and position accuracy in machines that rely on complex motion.

Removing the Barriers of Design, Sourcing, and Time

At Kollmorgen, we know that OEM engineers can achieve a lot more when obstacles aren't in the way. So, we clear obstacles in three important ways:

Integrating Standard and Custom Products

The optimal solution is often not clear-cut. Our application expertise allows us to modify standard products or develop totally custom solutions across our whole product portfolio so that designs can take flight.

Providing Motion Solutions, Not Just Components

As companies reduce their supplier base and focus their engineering manpower on the product design, they need a total system supplier with a wide range of integrated solutions. Kollmorgen offers complete solutions as well as motion subsystems that combine programming software, engineering services and best-in-class motion components.

Global Footprint

With direct sales, engineering support, manufacturing facilities, and distributors spanning the Americas, Europe, the Middle East, and Asia, we're close to OEMs worldwide. Our proximity helps speed delivery and lend support where and when they're needed.

Financial and Operational Stability

Kollmorgen is part of Regal Rexnord. A key driver in the growth of all Regal Rexnord segments is the Regal Rexnord Business System, which relies on the principle of "kaizen" – or continuous improvement. Using world-class tools, cross-disciplinary teams of exceptional people evaluate processes and develop plans that result in superior performance.

Kollmorgen: Your partner. In Motion.

Trademarks
AKD is a registered trademark of Kollmorgen Corporation
AKM is a registered trademark of Kollmorgen Corporation
Cartridge DDR is a registered trademark of Kollmorgen Corporation
EnDat is a registered trademark of Dr. Johannes Heidenhain GmbH
EtherCAT is a registered trademark and patented technology, licensed by Beckhoff Automation GmbH
Ethernet/IP is a registered trademark of ODVA, Inc.
Ethernet/IP Communication Stack: copyright (c) 2009, Rockwell Automation
sercos® is a registered trademark of sercos® international e.V.
HIPERFACE and HIPERFACE DSL are registered trademarks of Max Stegmann GmbH
PROFINET is a registered trademark of PROFIBUS and PROFINET International (PI)
SIMATIC is a registered trademark of SIEMENS AG
SpeedTec, ytec, itec and htec are registered trademarks of TE Connectivity Ltd.
Windows is a registered trademark of Microsoft Corporation

Table of Contents

▶ **AKM® Servo Motor Family** **4**
▶ **AKM Model Nomenclature** **10**
▶ **AKM Servo Motor Quick Guide** **14**
▶ **AKM Servo Motor Specifications** **16**
Performance Data, Motor Parameters, Dimensional Drawings and Data
AKM1x Series Motor Specifications 22
AKM2x Series Motor Specifications 24
AKM3x Series Motor Specifications 26
AKM4x Series Motor Specifications 28
AKM5x Series Motor Specifications 32
AKM6x Series Motor Specifications 34
AKM7x Series Motor Specifications 38
AKM8x Series Motor Specifications 40
▶ **Brake Option** **55**
▶ **AKM Feedback Options** **56**
▶ **AKM Servo Motor Connector Options** **64**
▶ **AKM Servo Motor Connector Pinouts** **64**
▶ **AKM Technical Guide** **70**
I. L10 Bearing Fatigue 70
II. Shaft Loading 72
III. Teflon Shaft Seals 72
IV. Thermal Sensor Protective Devices 73
V. Delta Between Motor Winding and Thermal Dev. 74
VI. Motor Phasing Diagram 74
▶ **Kollmorgen Solutions** **75**
Automation and Motion Control 75
Self-Help Tools 75

AKM® Servo Motor Family

Kollmorgen's AKM family of servo motors gives you unprecedented choice and flexibility from a wide range of standard products so you can select the best servo motor for your application.

With the broad range of AKM and AKM2G motors that support voltages up to 480 Vac, washdown, food grade, and the AKMH stainless steel hygienic motor for the toughest environments- Kollmorgen has a standard motor solution that can meet your needs right from the catalog.

Still need more? For your truly unique motion control applications, work with our engineering team to customize a solution for your machine design. Either way, standard product or customized, we can help you choose the motion control solution that meets your exact requirements.



The Benefits of AKM® Servo Motors

Best-in-Class Performance	» Industry-leading motor power density » Same size AKM/AKD system delivers up to 47% more shaft power » Compensation for stiff and compliant transmissions and couplings » Exceptionally low cogging
Flexibility to Find an Exact-fit Solution in a Standard Product	» AKM offers 28 frame-stack combinations and 120 standard windings in a single motor line » 4.8 million possible AKM part number combinations and growing » Simplifies or eliminates mechanical modifications and engineering adaptation » Available with single cable technology with digital feedback (Digital Resolver SFD3, SFD-M, or HIPERFACE® DSL) » Washdown and Food Grade options for AKM » Higher torque models up to 180 Nm of continuous torque
Ease-of-Use and Faster Commissioning	» Plug-and-play motor recognition drive commissioning » Reduce cycle time and sensor-and-wiring costs by eliminating traditional homing methods » Reduction in set-up time for each servo system

AKM® Servo Motor Family

AKM Motors Offer Extremely High Torque Density and High Acceleration

The AKM high-performance motor series offers a wide range of mounting, connectivity, feedback and other options. These motors offer superb flexibility to meet application needs with:

- 8 frame sizes (40 to 260 mm)
- 28 frame-stack length combinations
- More than 120 standard windings



Features

Torque
0.16 to 180 Nm continuous stall torque (1.4 to 1590 lb-in) in 28 frame/stack combinations. Specific torques are often available from multiple frame sizes to optimize mounting and inertia matching capabilities.

Speed
Speeds up to 8000 rpm meet high speed application requirements. Windings tailored to lower speeds are also available.

Voltage
AKM motors can be applied to all standard global voltages. Windings are specifically tailored to work with drives powered by 75 Vdc, 120, 240, 400 or 480 Vac.

Mounting
Multiple mounting standards are available to meet common European, North American, and Japanese standards.

Feedback
AKM motors include resolver, encoder (commutating), Sine-Absolute encoder or SFD (Smart Feedback Device) feedback options to meet specific application requirements.

Smoothness
Smooth performance results from low-cog, low-harmonic distortion magnetic designs.


Connectivity
Rotatable IP65 connectors, straight IP67 connectors or low cost IP20 Molex plugs are both available to provide flexibility. Single connectors/plugs (combined power and feedback) are also available to minimize motor and cable cost (SFD and DSL only).

Thermal
Windings are rated conservatively at 100°C rise over a 40°C ambient while using 155°C (class F) insulation materials. Motors meet applicable UL, CSA, and CE requirements and include thermistors.

Additional Options:

- » Holding Brakes
- » Shaft sealing options available
- » Feedback devices
- » Shaft and mounting variations
- » Custom windings
- » Connectivity

Kollmorgen AKM Configurable Servo Motor Features



Standard connector options available (i.e. IP67 straight, IP65 rotatable and cable)

Multiple stack lengths and windings available on each motor size

Shaft Sealing Options Available (IP54, IP65 and IP67 rated options)

Optional shaft and keyway configurations available

Rugged powder coating

Optional brake

Multiple feedback options available

Multiple standard mounts and customized options available

Insulation Class F, high torque density windings with thermal protection and linear thermal device options

Potted for increased thermal dissipation which yields higher performance in a small package

Low cogging design

EN60034-1
EN60034-5
E61960
PS155-1

AKM® Servo Motor Family


Offering a broad power range along with durability and economy



AKM1
Flange: NEMA 17 / 40 mm
Power: 0.08 - 0.30 kW
Max Speed: 8000 RPM
Stacks: 3



AKM2
Flange: NEMA 23 / 58 mm
Power: 0.10 - 0.94 kW
Max Speed: 8000 RPM
Stacks: 4



AKM3
Flange: 70 mm
Power: 0.09 - 1.31kW
Max Speed: 8000 RPM
Stacks: 3




AKM4
Flange: NEMA 34 / 84 mm
Power: 0.21- 1.73 kW
Max Speed: 6000 RPM
Stacks: 4




AKM5
Flange: NEMA 42 / 108 mm
Power: 0.56 - 3.87 kW
Max Speed: 6000 RPM
Stacks: 4



AKM6
Flange: 138 mm
Power: 1.17 - 6.24 kW
Max Speed: 6000 RPM
Stacks: 4



AKM7
Flange: 188 mm
Power: 3.97 - 8.58 kW
Max Speed: 6000 RPM
Stacks: 3



AKM8
Flange: 260 mm
Power: 12.4 - 19.8 kW
Max Speed: 3000 RPM
Stacks: 3

AKM® Washdown and Food Grade

These motor variants are used in applications that are subject to strict hygiene regulations in which it is essential that the formation of nuclei and corrosion are avoided and in which machines must be cleaned cyclically. These motors are based on the standard types AKM2 – AKM6 with special modifications for use in the food-processing industry, in the packaging industry, or even outdoors. An option for AKM Washdown and Food Grade motors is to coat the flange.

AKM® Washdown

Part Numbers:
AKMxxx-xxxxx-0W: Washdown with unpainted flange
AKMxxx-Wxxxx-0W: Washdown with painted flange

Note: The AKM Washdown motors must not come into contact with any unpacked food.



Application Area:	Harsh Environments, Outdoors
Application Examples:	Transport in the food and packaging area without contact with food, radar stations, and wind turbines
Standards:	UL, CSA, CE, RoHS
Surface:	Gray 2K paint
Immunity:	Against tested industrial cleaning agents*, corrosion-resistant
Degree of Protection:	IP67
Shaft:	303 Stainless steel (CSN417029)
Rotary Shaft Seal:	PTFE
Lubricant:	Industrial bearing grease, non-food-grade
Connector:	Stainless steel, smooth surface
Screws:	Stainless steel
Name Plate:	Engraved, additional name plate in the package

AKM® Food Grade

Part Numbers:
AKMxxx-xxxxx-0F: Food Grade with unpainted flange
AKMxxx-Wxxxx-0F: Food Grade with painted flange

Note: The surface of the AKM Food Grade food motor has passed all tests as per FDA Global Migration for indirect contact with food. Any direct contact with unpacked food is not permitted.



Application Examples:	Food and beverages industries; cutting, packing, and filling without direct contact with food; motor positioned laterally or below the food.
Standards:	UL, CSA, CE, RoHS, FDA
Surface:	White 2K FDA compliant paint**
Immunity:	Against tested industrial cleaning agents*, corrosion-resistant
Degree of Protection:	IP67
Shaft:	303 Stainless steel (CSN417029)
Rotary Shaft Seal:	PTFE as per FDA
Lubricant:	Food grade as per FDA
Connector:	Stainless steel, smooth surface
Screws:	Stainless steel
Name Plate:	Engraved, additional name plate in the package

* Resistance of the AKM Washdown and AKM Food Grade surfaces to the following industrial cleaning agents has been tested: P3-topactive DES, P3-topactive LA, P3-topax 56, P3-topax 66, P3-topax 91
**Meets FDA global migration standards

AKM® Model Nomenclature

AKM® Brushless Servo Motor

AKM 6 2 P – A N C N DA 00

AKM Series

Flange Size

1	40 mm
2	58 mm
3	70 mm
4	84 mm
5	108 mm
6	138 mm
7	188 mm
8	260 mm

Rotor Stack Length

		AKMx Availability							
		1	2	3	4	5	6	7	8
1	1 stack	•	•	•	•	•			
2	2 stacks	•	•	•	•	•	•	•	•
3	3 stacks	•	•	•	•	•	•	•	•
4	4 stacks		•		•	•	•	•	•
5	5 stacks						•		

Winding Type

A to Z

S Special

Mount

A	IEC with tolerance N
B	NEMA
C	Alternative IEC standard
D	Other standard
G	Alternative IEC standard
H	Alternative IEC standard
R	IEC with tolerance R
M, T	Reinforced bearing AKM8
W	Flange coating for Washdown, IEC
S	Special

Shaft

C	Keyway
K	Open keyway
N	Smooth shaft
S	Special

Customization/Seal

00	Standard motor without shaft seal (IP54 rating)
01	With shaft seal (IP65 rating)
0F	Food Grade (IP67 rating)
0W	Washdown (IP67 rating)
XX	Customization

Feedback Device

For all options see following page

S Special

Brake

2	24 V holding brake
N	Without brake
S	Special

Connectors

For all option details see following page

B	Dual 90° M23 Intercontec connectors, motor-mounted (AKM2 only)
C	Dual straight M23 Intercontec connectors, on 0.5 m shielded leads (AKM1-AKM2)
C	Dual 90° M23 Intercontec connectors, motor-mounted (AKM3-AKM7)
9	Single 90° itec connector, motor-mounted (AKM1 only)
9	Single 90° M23 Intercontec connector, motor-mounted (AKM2-AKM6)
G	Dual straight M23 Intercontec connector, motor-mounted (AKM2-AKM7)
H	Dual 90° M40 Intercontec connector and M23 Intercontec feedback connector, motor-mounted (AKM74QT & AKM82T)
M	Dual molex connectors, on 0.5 m shielded leads (AKM1-AKM4)
P	Single Molex connector, on 0.5 m shielded leads (AKM1-AKM4)
T	Dual terminal box for power and M23 Intercontec feedback connector, motor-mounted (AKM8)
Y	Single ytec connector, motor-mounted (AKM1 only)

Note: These connector options are only valid for the "00" and "01" customization/seal option variants. Stainless Steel Hummel connectors are used for AKM Washdown (0W) and AKM Food Grade (OF) variants.

Base Model	Mount-Shaft Availability																								
	AC	AK	AN	BK	BN	CC	CK	CN	DC	DK	DN	EF	EK	EN	GC	GN	HC	HN	KK	LK	MC	MN	TC	TN	WC	WN
AKM1		•	•		•		•	•																		
AKM2	•		•		•		•		•		•	•		•											•	•
AKM3	•		•			•		•							•	•									•	•
AKM4	•		•	•		•		•					•		•	•			•						•	•
AKM5	•		•	•		•		•		•			•		•	•									•	•
AKM6	•		•												•	•			•	•					•	•
AKM7	•		•												•	•			•							
AKM8	•		•			•		•							•	•	•	•			•	•	•	•		

Note: Options shown in blue text are considered standard.

Feedback Unit Options

Code	Designation	AKM Frame Size	Single-Turn or Multi-Turn	Feedback Resolution: Device Resolution (Sin/Cos per Rev., Bits or Lines/Rev.)	Feedback Resolution: AKD Internal Resolution	Feedback Resolution: AKD2G Internal Resolution	Feedback Resolution: # of Absolute Revs.	Feedback Resolution: Accuracy (± arc-mins)
1-	Commutating Encoder	1-8	Single-Turn	1024 Lines	4,096	4,096	None	1
2-				2048 Lines	8,192	8,192		
ED		2-8		500 Lines	2,000	2,000		
EE				1000 Lines	4,000	4,000		
EF				2000 Lines	8,000	8,000		
EG				2500 Lines	10,000	10,000		
EH				5000 Lines	20,000	20,000		
EJ				10000 Lines	40,000	40,000		
EM				4096 Lines	16,384	16,384		
EN				8192 Lines	32,768	32,768		
AA	BiSS B Optical Sine Encoder	2-4	Single-turn	2048 Sin/Cos	27-Bits	32-Bits	1	0.6
		5-8						
AB		2-4	Multi-turn				4,096	
		5-8						
C-	SFD Smart Feedback Device	1	Single-turn	24-Bits	24-Bits	24-Bits	1	15
		2-4						8
		5-8						9
CA	SFD3 Smart Feedback Device, Gen. 3	1	Single-turn	24-Bits				15
		2-4						8
		5-6						9
CB	SFD-M Smart Feedback Device, Multi-turn	2-6	Multi-turn	24-Bits	24-Bits	24-Bits	65,536	1
GE	HIPERFACE DSL® Optical Encoder	2-6	Single-turn	18-Bits	18-Bits	18-Bits	1	1.33
GF			Multi-turn				4,096	
GA/GJ*	HIPERFACE Optical Sin/Cos Encoder	2-8	Single-turn	128 Sin/Cos	23-Bits	31-Bits	1	1.33
GB/GK*			Multi-turn				4,096	
GP**	HIPERFACE Capacitive Encoder	1	Single-turn	16 Sin/Cos	20-Bits	28-Bits	1	4.8
GR**			Multi-turn				4,096	
DA	EnDat® 2.2/01 Optical Sine Encoder	2-4	Single-turn	512 Sin/Cos	25-Bits	32-Bits	1	1
		5-8		2048 Sin/Cos	27-Bits			0.333
DB		2-4	Multi-turn	512 Sin/Cos	25-Bits		4,096	1
		5-8		2048 Sin/Cos	27-Bits			0.333
LA	EnDat® 2.2/22 Inductive Encoder	2-3	Single-turn	18-Bits	18-Bits	18-Bits	1	4.67
		4-8		19-Bits	19-Bits	19-Bits		3
LB		2-3	Multi-turn	18-Bits	18-Bits	18-Bits	4,096	4.67
		4-8		19-Bits	19-Bits	19-Bits		3
R-	Resolver Inductive Encoder	1	Single-Turn	1 pole pair (16-Bits)	16-Bits	16-Bits	1	15
		2-4						10
		5-8						9

*ServoStar (Sxxx)/AKD mapped respectively
**AKD mapped ONLY

Related Resources:
Feedback Option Specifications
Connector Options and Pinouts
Thermal Device Options

Connector Options

Code	Thermal Sensor*	Used with	IP Rating**	Connection type	Description
B	PTC	AKM2	IP65	2 SpeedTec Ready connectors, size 1.0 (M23)	Angled, rotatable, mounted on motor
C	PTC	AKM1-AKM2	IP65	2 SpeedTec Ready connectors, size 1.0 (M23)	On 0.5m cable
C	PTC	AKM3-AKM7	IP65	2 SpeedTec Ready connectors, size 1.0 (M23)	Angled, rotatable, mounted on motor
9	PT1000	AKM1	IP65	1 hybrid itec connector	Rotatable, mounted on motor
9	PT1000	AKM2-AKM6	IP65	1 SpeedTec Ready connector, size 1.0 (M23)	Angled, rotatable, mounted on motor
G	PTC	AKM2-AKM7	IP67	2 SpeedTec Ready connectors, size 1.0 (M23)	Straight, mounted on motor
H	PTC	AKM7 & AKM82T	IP65	1 feedback threaded connector, size 1.0 (M23) 1 power threaded connector, size 1.5 (M40)	Angled, rotatable, mounted on motor
M	PTC	AKM1-AKM4	IP20	2 Molex connectors, I_c < 6 A	On 0.5m cable
P	PTC	AKM1-AKM4	IP20	1 Molex connector, I_c < 6 A	On 0.5m cable
T	PTC	AKM8	IP65	1 terminal box for power 1 feedback threaded connector, size 1.0 (M23)	Mounted on motor
Y	PTC	AKM1	IP65	1 ytec connector	Rotatable, mounted on motor

NOTE: These connector options are only valid for the "00" or "01" Customization/Seal Option variants. Stainless Steel Hummel connectors are used for AKM Washdown (0W) and AKM Food Grade (0F) variants.

*For Thermal Device Curves, reference see the Thermal Sensor Protective Devices page.
**IP ratings shown apply ONLY to the connector and the connector base/bushing on motor.

AKM® Model Nomenclature

Feedback and Connector Availability

AKM1

Feedback Code	Connector Code: C	9	M	P	Y
R-	•		•		•
1-, 2-	•		•		•
C-	•		•	•	•
CA		•			
GP, GR	•				•

AKM2

Feedback Code	Connector Code: B	C	9	G	M	P
R-	•	•		•	•	
1-, 2-	•	•		•	•	
Ex	•	•		•	•	
AA, AB	•	•		•	•	
C-	•	•	•	•	•	•
CA,CB			•			
DA,DB	•	•		•	•	
LA, LB	•	•		•	•	
GA, GB	•			•		
GE, GF			•			
GJ, GK	•			•		

AKM3

Feedback Code	Connector Code: C	9	G	M	P
R-	•		•	•	
1-, 2-	•		•	•	
Ex	•		•	•	
AA, AB	•		•	•	
C-	•	•	•	•	•
CA,CB		•			
DA,DB	•		•	•	
LA, LB	•		•	•	
GA, GB	•		•		
GE, GF		•			
GJ, GK	•		•		

AKM4

Feedback Code	Connector Code: C	9	G	M	P
R-	•		•	•	
1-, 2-	•		•	•	
Ex	•		•	•	
AA, AB	•		•	•	
C-	•	•	•	•	•
CA,CB		•			
DA,DB	•		•	•	
LA, LB	•		•	•	
GA, GB	•		•		
GE, GF		•			
GJ, GK	•		•		

AKM5

Feedback Code	Connector Code: C	9	G
R-	•		•
1-, 2-	•		•
Ex	•		•
AA, AB	•		•
C-	•		•
CA,CB		•	
DA,DB	•		•
LA, LB	•		•
GA, GB	•		•
GE, GF		•	
GJ, GK	•		•

AKM6

Feedback Code	Connector Code: C	9	G
R-	•		•
1-, 2-	•		•
Ex	•		•
AA, AB	•		•
C-	•		•
CA,CB		•	
DA,DB	•		•
LA, LB	•		•
GA, GB	•		•
GE, GF		•	
GJ, GK	•		•

AKM7

Feedback Code	Connector Code: C	G	H*
R-	•	•	•
1-, 2-	•	•	•
Ex	•	•	•
AA, AB	•	•	•
C-	•	•	•
DA,DB	•	•	•
LA, LB	•	•	•
GA, GB	•	•	•
GJ, GK	•	•	•

*AKM74Q Only

AKM8

Feedback Code	Connector Code: H*	T
R-	•	•
1-, 2-	•	•
Ex	•	•
AA, AB	•	•
C-	•	•
DA,DB	•	•
LA, LB	•	•
GA, GB	•	•
GJ, GK	•	•

*AKM82T Only

Related Resources:
Feedback Option Specifications
Connector Options and Pinouts

AKM® Tested with AKD Servo Drives

The AKM performance data and curves in this guide were acquired using Kollmorgen's AKD family of servo drives. Please go to https://www.kollmorgen.com/en-us/products/drives/servo/servo-drives or contact Kollmorgen Customer Support for detailed specifications and to learn how pairing them with the AKM servo motor can optimized system peformance.

AKD® Product Family



Parameter	AKD2G	AKD	AKD BASIC	AKD PDMM	AKD-N/AKD-C
Base I/O	12 digital 2 analog	11 digital 2 analog	11 digital 2 analog	17 digital 2 analog	5 digital
Expansion I/O[1]	8 digital 2 analog *Drive size is the same	No	20 digital 2 analog *adds 30 mm to the drive width for drives up to 12A	Up to 1000+ remote I/O via EtherCAT	No
Safe I/O	2 digital inputs for Safey option 1 4 digital inputs for SafeMotion options	No	No	No	No
SafeMotion[2]	Yes	STO only	STO only	STO only	STO only
Optimized for single cable[3]	Yes	No	No	No	Yes
Continuous current limit[4]	24A	48A	48A	48A	12A
Connectivity[5]	Analog, EtherCAT, CANopen, Profinet IRT, Ethernet/IP, TCP/IP, Modbus/TCP	Analog, EtherCAT, CANopen, Profinet RT, Ethernet/IP, TCP/IP, Modbus/TCP	Analog	EtherCAT, CANopen, Profinet RT, Ethernet/IP, TCP/IP, Modbus/TCP	EtherCAT
Axis Configuration	single or dual	single	single	single	single
Drive-resident controller	No	No	No	Yes	No
Programmability	parameterized, 2 axes control loops, actlon table	parameterized	parameterized, BASIC programmable	parameterized, IEC 61131-3 via PLCo-pen or Pipe Network	parameterized
Graphical Display	160x128-pixel display	2 digit LED	2 digit LED	3 digit LED	Status LED
Removeable Memory[6]	Yes	No	Yes	Yes	No
System Architecture	Centralized	Centralized	Centralized	Centralized	Decentralized
IP Rating	IP20	IP20	IP20	IP20	IP67 (AKD-N)

Notes:
1: Add EtherCAT multi-axis master, PCMM, to the AKD drive family to enable remote I/O expansion via EtherCAT. PCMM controller functionality is built into the PDMM
2: SafeMotion includes FSoE, STO, SS1, SS2, SOS, SDB, SBC/SBT, SLS, SSR, SSM, SDI, SAR, SLA, SLI, SLP, SCA up to SIL3 / PLe
3: Single cable optimized means one single cable for power & motor feedback with 1 connector at motor end and 1 connector at drive end
4: Higher power variants under development in some models. Consult factory for availability.
5: Consult factory on connectivity options for AKD2G. Profinet and Ethernet/IP will be added in 2021
6: Optional integrated SD card for easy backup and drive cloning

AKM® Servo Motor Quick Guide

AKM, AKM Washdown, and AKM Food Grade

Performance Data

AKM Servo Motor	Flange size [mm]	Cont. Torque at Stall Tcs [Nm]	Continuous Current I_0 [A]	Peak Torque at stall Tps [Nm]	75 Vdc			120 Vac (160 Vdc)			240 Vac (320 Vdc)			400 Vac (560 Vdc)			480 Vac (640 Vdc)			Inertia (Jm) [kg•cm²]	Weight [kg]
					Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]	Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]	Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]	Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]	Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]		
11B	40	0.18	1.16	0.61	–	–	–	4000	0.18	0.08	8000	0.17	0.14	–	–	–	–	–	–	0.017	0.35
11C	40	0.18	1.45	0.61	–	–	–	6000	0.18	0.11	–	–	–	–	–	–	–	–	–	0.017	0.35
11E	40	0.18	2.91	0.61	6000	0.18	0.11	–	–	–	–	–	–	–	–	–	–	–	–	0.017	0.35
12C	40	0.31	1.51	1.08	–	–	–	4000	0.30	0.13	8000	0.28	0.23	–	–	–	–	–	–	0.031	0.49
12E	40	0.31	2.72	1.05	3000	0.31	0.10	8000	0.28	0.23	–	–	–	–	–	–	–	–	–	0.031	0.49
13C	40	0.41	1.48	1.46	–	–	–	3000	0.41	0.13	8000	0.36	0.30	–	–	–	–	–	–	0.045	0.63
13D	40	0.40	2.40	1.44	2000	0.40	0.08	7000	0.36	0.27	–	–	–	–	–	–	–	–	–	0.045	0.63
21C	58	0.48	1.58	1.47	–	–	–	2500	0.46	0.12	8000	0.39	0.32	–	–	–	–	–	–	0.11	0.82
21E	58	0.50	3.11	1.49	2000	0.48	0.10	7000	0.41	0.30	–	–	–	–	–	–	–	–	–	0.11	0.82
21G	58	0.50	4.87	1.51	4000	0.46	0.19	–	–	–	–	–	–	–	–	–	–	–	–	0.11	0.82
22C	58	0.84	1.39	2.73	–	–	–	1000	0.83	0.09	3500	0.78	0.29	8000	0.68	0.57	8000	0.68	0.57	0.16	1.10
22E	58	0.87	2.73	2.76	1000	0.85	0.09	3500	0.81	0.30	8000	0.70	0.59	–	–	–	–	–	–	0.16	1.10
22G	58	0.88	4.82	2.79	2500	0.83	0.22	7000	0.74	0.54	–	–	–	–	–	–	–	–	–	0.16	1.10
23C	58	1.13	1.41	3.81	–	–	–	1000	1.11	0.12	2500	1.08	0.28	5500	0.99	0.57	7000	0.95	0.70	0.22	1.38
23D	58	1.16	2.19	3.84	–	–	–	1500	1.12	0.18	5000	1.03	0.54	8000	0.92	0.77	8000	0.92	0.77	0.22	1.38
23E	58	1.16	2.78	3.86	–	–	–	2500	1.1	0.29	6500	0.98	0.67	8000	0.87	0.73	–	–	–	0.22	1.38
23F	58	1.18	4.31	3.88	1500	1.15	0.18	4500	1.07	0.50	8000	0.94	0.79	–	–	–	–	–	–	0.22	1.38
24C	58	1.38	1.42	4.73	–	–	–	–	–	–	2000	1.32	0.28	4500	1.25	0.59	5500	1.22	0.70	0.27	1.66
24D	58	1.41	2.21	4.76	–	–	–	1500	1.36	0.21	4000	1.29	0.54	8000	1.11	0.93	8000	1.11	0.93	0.27	1.66
24E	58	1.40	2.79	4.79	–	–	–	2000	1.34	0.28	5500	1.24	0.71	8000	1.12	0.82	–	–	–	0.27	1.66
24F	58	1.42	3.89	4.82	1000	1.39	0.15	3000	1.33	0.42	8000	1.12	0.94	–	–	–	–	–	–	0.27	1.66
31C	70	1.15	1.37	3.88	–	–	–	–	–	–	2500	1.12	0.29	5000	1.00	0.52	6000	0.91	0.57	0.33	1.55
31E	70	1.20	2.99	4.00	750	1.19	0.09	2500	1.17	0.31	6000	0.95	0.60	–	–	–	–	–	–	0.33	1.55
31H	70	1.23	5.85	4.06	2000	1.20	0.25	6000	0.97	0.61	–	–	–	–	–	–	–	–	–	0.33	1.55
32C	70	2.00	1.44	6.92	–	–	–	–	–	–	1500	1.95	0.31	3000	1.86	0.58	3500	1.83	0.67	0.59	2.23
32D	70	2.04	2.23	7.10	–	–	–	1000	2.00	0.21	2500	1.93	0.51	5500	1.65	0.95	6000	1.58	0.99	0.59	2.23
32E	70	2.04	2.82	7.11	–	–	–	–	–	–	3500	1.87	0.69	7000	1.41	1.03	7000	1.22	1.02	0.59	2.23
32H	70	2.10	5.50	7.26	1200	2.06	0.26	3000	1.96	0.62	7000	1.45	1.06	–	–	–	–	–	–	0.59	2.23
33C	70	2.71	1.47	9.76	–	–	–	–	–	–	1000	2.64	0.28	2000	2.54	0.53	2500	2.50	0.65	0.85	2.9
33E	70	2.79	2.58	9.96	–	–	–	–	–	–	2000	2.62	0.55	4500	2.34	1.10	5000	2.27	1.19	0.85	2.9
33H	70	2.88	5.62	10.22	800	2.82	0.24	2500	2.66	0.70	5500	2.27	1.31	–	–	–	–	–	–	0.85	2.9
41C	84	1.95	1.46	6.12	–	–	–	–	–	–	1200	1.88	0.24	3000	1.77	0.56	3500	1.74	0.64	0.81	2.44
41E	84	2.02	2.85	6.28	–	–	–	1200	1.94	0.24	3000	1.82	0.57	6000	1.58	0.99	6000	1.58	0.99	0.81	2.44
41H	84	2.06	5.6	6.36	1000	1.99	0.21	3000	1.86	0.58	6000	1.62	1.02	–	–	–	–	–	–	0.81	2.44
42C	84	3.35	1.40	11.3	–	–	–	–	–	–	–	–	–	1500	3.10	0.49	2000	3.02	0.63	1.5	3.39
42E	84	3.42	2.74	11.3	–	–	–	–	–	–	1800	3.12	0.59	3500	2.81	1.03	4000	2.72	1.14	1.5	3.39
42G	84	3.53	4.80	11.5	–	–	–	–	–	–	3500	2.90	1.06	6000	2.35	1.48	6000	2.35	1.48	1.5	3.39
42H	84	3.54	5.90	11.6	–	–	–	2000	3.2	0.67	4500	2.72	1.28	–	–	–	–	–	–	1.5	3.39
42J	84	3.56	8.4	11.6	–	–	–	3000	3.03	0.95	6000	2.36	1.50	–	–	–	–	–	–	1.5	3.39
43E	84	4.70	2.76	15.9	–	–	–	–	–	–	1500	4.24	0.67	2500	3.92	1.03	3000	3.76	1.18	2.1	4.35
43G	84	4.80	4.87	16.1	–	–	–	–	–	–	2500	4.00	1.05	5000	3.01	1.58	6000	2.57	1.61	2.1	4.35
43H	84	4.82	5.40	16.1	–	–	–	1200	4.46	0.56	3000	3.86	1.21	5500	2.81	1.62	–	–	–	2.1	4.35
43K	84	4.90	9.60	16.4	–	–	–	2500	4.08	1.07	6000	2.62	1.65	–	–	–	–	–	–	2.1	4.35
43L	84	4.73	11.2	16.0	–	–	–	3000	3.78	1.19	6000	2.53	1.59	–	–	–	–	–	–	2.1	4.35
44E	84	5.76	2.90	19.9	–	–	–	–	–	–	1200	5.22	0.66	2000	4.80	1.01	2500	4.56	1.19	2.7	5.3
44G	84	5.88	5.00	20.2	–	–	–	–	–	–	2000	4.90	1.03	4000	3.76	1.57	5000	3.19	1.67	2.7	5.3
44H	84	5.89	5.6	20.0	–	–	–	–	–	–	2500	4.66	1.22	5000	3.19	1.67	6000	2.70	1.70	2.7	5.3
44J	84	6.00	8.80	20.4	–	–	–	–	–	–	4000	3.84	1.61	6000	2.75	1.73	6000	2.75	1.73	2.7	5.3
44K	84	5.88	10.1	20.2	–	–	–	2000	4.9	1.03	5000	3.18	1.67	–	–	–	–	–	–	2.7	6.3
51E	108	4.70	2.75	11.6	–	–	–	–	–	–	1200	4.41	0.55	2500	3.98	1.04	3000	3.80	1.19	3.4	4.2
51G	108	4.75	4.84	11.7	–	–	–	–	–	–	2500	4.02	1.05	5000	2.62	1.37	6000	1.94	1.22	3.4	4.2
51H	108	4.79	6.00	11.7	–	–	–	–	–	–	3000	3.87	1.22	6000	1.95	1.23	6000	1.95	1.23	3.4	4.2
51K	108	4.90	9.40	11.9	–	–	–	2500	4.15	1.09	5500	2.35	1.35	–	–	–	–	–	–	3.4	4.2
51L	108	4.89	11.9	12	–	–	–	3000	3.95	1.24	6000	2.00	1.26	–	–	–	–	–	–	3.4	4.2

Performance curves can be generated using our online Performance Curve Generator Tool

Performance Data (continued)

AKM Servo Motor	Frame size [mm]	Cont. Torque at Stall Tcs [Nm]	Continuous Current I_0 [A]	Peak Torque at stall Tps [Nm]	120 Vac (160 Vdc)			240 Vac (320 Vdc)			400 Vac (560 Vdc)			480 Vac (640 Vdc)			Inertia (Jm) [kg•cm²]	Weight [kg]
					Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]	Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]	Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]	Rated Speed Nrtd [RPM]	Rated Torque Trtd [Nm]	Rated Power Prtd [kW]		
52E	108	8.34	2.99	21.3	–	–	–	–	–	–	1500	7.61	1.20	2000	7.28	1.52	6.2	5.8
52G	108	8.43	4.72	21.5	–	–	–	1500	7.69	1.21	2500	7.06	1.85	3000	6.66	2.09	6.2	5.8
52H	108	8.48	5.90	21.6	–	–	–	1800	7.53	1.42	3500	6.26	2.30	4000	5.77	2.42	6.2	5.8
52K	108	8.60	9.30	21.9	–	–	–	3000	6.80	2.14	5500	3.90	2.25	6000	3.25	2.04	6.2	5.8
52L	108	8.67	11.6	22.0	–	–	–	3500	6.40	23.5	6000	3.27	2.06	6000	3.27	2.03	6.2	5.8
52M	108	8.60	13.1	21.9	2000	7.5	1.57	4500	5.20	2.45	–	–	–	–	–	–	6.2	5.8
53G	108	11.4	4.77	29.9	–	–	–	1000	10.7	1.12	2000	9.85	2.06	2400	9.50	2.39	9.1	7.4
53H	108	11.5	6.60	30.0	–	–	–	–	–	–	3000	8.63	2.77	3500	8.23	3.02	9.1	7.4
53K	108	11.6	9.40	30.3	–	–	–	2000	10.1	2.12	4000	7.65	3.20	4500	6.85	3.23	9.1	7.4
53L	108	11.6	11.8	30.3	–	–	–	3000	8.9	2.80	5500	5.00	2.88	6000	4.05	2.55	9.1	7.4
53M	108	11.4	13.4	29.7	–	–	–	3000	8.72	2.74	–	–	–	–	–	–	9.1	7.4
53P	108	11.4	19.1	29.8	–	–	–	5000	5.88	3.08	–	–	–	–	–	–	9.1	7.4
53Q	108	11.57	21.1	30.2	2500	9.58	2.51	5500	4.99	2.87	–	–	–	–	–	–	9.1	7.4
54G	108	14.3	5.00	38.0	–	–	–	–	–	–	1500	12.9	2.03	2000	12.3	2.57	12	9
54H	108	14.2	5.50	37.5	–	–	–	1000	13.4	1.40	1800	12.6	2.38	2000	12.2	2.56	12	9
54K	108	14.4	9.7	38.4	–	–	–	1800	12.7	2.39	3500	10.0	3.68	4000	9.25	3.87	12	9
54L	108	14.1	12.5	37.5	–	–	–	2500	11.5	3.00	4500	8.13	3.83	–	–	–	12	9
54N	108	14.1	17.8	37.6	1500	12.8	2.01	3500	9.85	3.61	–	–	–	–	–	–	12	9
54P	108	14.36	19.6	38.04	2000	12.4	3.63	4000	9.23	3.87	–	–	–	–	–	–	12	9
62G	138	11.9	4.9	29.7	–	–	–	–	–	–	1800	10.4	1.96	2000	10.2	2.14	17	8.9
62H	138	11.9	5.4	29.6	–	–	–	1000	11.2	1.17	2000	10.2	2.14	2400	9.9	2.49	17	8.9
62K	138	12.2	9.6	30.2	–	–	–	2000	10.4	2.18	3500	9.00	3.30	4500	8.00	3.77	17	8.9
62L	138	12.2	12.0	30.1	–	–	–	2500	10.0	2.62	5000	7.42	3.89	6000	5.74	3.61	17	9.8
62M	138	12.2	13.4	30.2	–	–	–	3000	9.50	2.98	6000	5.70	3.58	6000	5.70	3.58	17	8.9
62P	138	12.3	18.8	30.3	–	–	–	4500	8.10	3.82	–	–	–	–	–	–	17	8.9
62Q	138	12.0	21.8	29.8	–	–	–	5500	6.5	3.74	–	–	–	–	–	–	17	8.9
63G	138	16.5	4.5	41.8	–	–	–	–	–	–	1200	14.9	1.87	1500	14.6	2.29	24	11.1
63H	138	16.6	5.6	42.1	–	–	–	–	–	–	1500	14.6	2.29	1800	14.2	2.68	24	11.1
63K	138	16.8	9.9	42.6	–	–	–	1500	14.9	2.34	3000	12.9	4.05	3500	12.0	4.40	24	11.1
63L	138	16.8	11.1	42.6	–	–	–	1800	14.4	2.71	3000	12.9	4.05	3500	12	4.4	24	11.1
63M	138	17.0	13.8	43.0	–	–	–	2000	14.3	2.99	4000	11.3	4.73	4500	10.5	4.95	24	11.1
63N	138	17.0	17.4	43.0	–	–	–	3000	13.0	4.08	5000	9.60	5.03	6000	7.00	4.40	24	11.1
63Q	138	16.7	22.4	42.4	–	–	–	3500	11.9	4.36	–	–	–	–	–	–	24	11.1
64K	138	20.8	9.2	53.5	–	–	–	1200	18.8	2.36	2000	17.2	3.60	2500	16.3	4.27	32	13.3
64L	138	21.0	12.8	54.1	–	–	–	1500	18.4	2.89	3000	15.6	4.90	3500	14.4	5.28	32	13.3
64P	138	20.4	18.6	52.9	–	–	–	2500	16.0	4.19	4500	11.9	5.62	5500	9.00	5.18	32	13.3
64Q	138	20.6	20.7	53.2	–	–	–	3000	15.3	4.81	5000	10.7	5.60	6000	7.40	4.65	32	13.3
65K	138	24.8	9.8	64.5	–	–	–	1000	22.8	2.39	2000	20.2	4.23	2200	19.7	4.54	40	15.4
65L	138	25.0	12.2	65.2	–	–	–	1300	22.4	3.05	2500	19.2	5.03	2800	18.6	5.37	40	15.4
65M	138	25.0	13.6	65.2	–	–	–	1500	21.9	3.44	2700	18.8	5.32	3000	18.1	5.69	40	15.4
65N	138	24.3	17.8	63.7	–	–	–	2000	19.8	4.15	3500	16.0	5.86	4000	14.7	6.16	40	15.4
65P	138	24.5	19.8	64.1	–	–	–	2400	19.1	4.8	4000	14.9	6.24	5000	11.6	6.08	40	15.4
72K	188	29.7	9.3	79.4	–	–	–	–	–	–	1500	25.1	3.94	1800	24.0	4.52	65	19.7
72L	188	30	11.5	79.5	–	–	–	–	–	–	1800	24.3	4.58	2000	23.6	4.94	65	19.7
72M	188	30.0	13.0	79.8	–	–	–	–	–	–	2000	23.6	4.94	2500	22.1	5.79	65	19.7
72P	188	29.4	18.7	78.5	–	–	–	1800	23.8	4.49	3000	20.1	6.31	3500	18.2	6.67	65	19.7
72Q	188	29.5	23.5	78.4	–	–	–	2000	23.2	4.89	4000	16.3	6.83	4500	14.1	6.65	65	19.7
73L	188	42.0	12.1	113	–	–	–	–	–	–	1400	34.4	5.04	1500	33.8	5.31	92	26.7
73M	188	42.0	13.6	112	–	–	–	–	–	–	1500	33.8	5.31	1800	32.1	6.05	92	26.7
73P	188	41.6	19.5	111	–	–	–	1300	34.7	4.72	2400	28.5	7.16	2800	26.3	7.71	92	26.7
73Q	188	41.5	24.5	111	–	–	–	1500	33.4	5.25	3000	25.2	7.92	3500	22	8.07	92	26.7
74L	188	53.0	12.9	143	–	–	–	–	–	–	1200	43.5	5.47	1400	41.5	6.08	120	33.6
74P	188	52.5	18.5	142	–	–	–	–	–	–	1800	39.6	7.46	2000	35.9	7.52	120	33.6
74Q	188	52.2	26.1	141	–	–	–	1300	41.9	5.71	2500	31.5	8.25	3000	27.3	8.58	120	33.6
82T	260	75	48	175	–	–	–	–	–	–	2500	47.5	12.4	3000	38.0	11.9	172	49
83T	260	130	65	310	–	–	–	–	–	–	2200	70.0	16.1	2500	60.0	15.7	334	73
84T	260	180	67	434	–	–	–	–	–	–	1800	105	19.8	2000	93.0	19.5	495	97

Performance curves can be generated using our online Performance Curve Generator Tool

AKM1x Series Motor Specifications

AKM1x Performance Data – Up to 240 Vac (320 Vdc Bus) voltage

					AKM11			AKM12		AKM13	
	Parameters	Tol	Symbol	Units	B	C	E	C	E	C	D
	Max Rated Voltage ⑩	Max	–	Vac	240	120	–	240	120	240	120
				Vdc	320	160	75	320	160	320	160
	Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧	Nom	T_{cs}	Nm	0.183	0.185	0.185	0.310	0.310	0.409	0.401
				lb-in	1.62	1.64	1.64	2.75	2.71	3.62	3.55
	Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧	Nom	I_{cs}	A_{rms}	1.16	1.45	2.91	1.51	2.72	1.48	2.40
	Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	0.146	0.148	0.148	0.248	0.248	0.327	0.320
				lb-in	1.29	1.31	1.31	2.19	2.19	2.89	2.83
	Max Mechanical Speed ⑤	Nom	N_{max}	rpm	8000	8000	8000	8000	8000	8000	8000
	Peak Torque ①②	Nom	T_p	Nm	0.61	0.61	0.61	1.08	1.05	1.46	1.44
				lb-in	5.39	5.43	5.41	9.6	9.3	12.9	12.7
	Peak Current	Nom	I_p	A_{rms}	4.65	5.79	11.7	6.06	10.9	5.93	9.6
75 Vdc	Rated Torque (speed) ①②⑦⑧		T_{rtd}	Nm	-	-	0.176	-	0.305	-	0.401
				lb-in	-	-	1.56	-	2.7	-	3.55
	Rated Speed		N_{rtd}	rpm	-	-	6000	-	3000	-	2000
	Rated Power (speed) ①②⑦		P_{rtd}	kW	-	-	0.11	-	0.10	-	0.08
				Hp	-	-	0.15	-	0.13	-	0.11
120 Vac (160 Vdc)	Rated Torque (speed) ①②⑦⑧		T_{rtd}	Nm	0.180	0.176	-	0.304	0.275	0.407	0.365
				lb-in	1.59	1.56	-	2.69	2.43	3.60	3.23
	Rated Speed		N_{rtd}	rpm	4000	6000	-	4000	8000	3000	7000
	Rated Power (speed) ①②⑦		P_{rtd}	kW	0.08	0.11	-	0.13	0.23	0.13	0.27
				Hp	0.10	0.15	-	0.17	0.31	0.17	0.36
240 Vac (320 Vdc)	Rated Torque (speed) ①②⑦⑧		T_{rtd}	Nm	0.167	-	-	0.279	-	0.364	-
				lb-in	1.48	-	-	2.47	-	3.22	-
	Rated Speed		N_{rtd}	rpm	8000	-	-	8000	-	8000	-
	Rated Power (speed) ①②⑦		P_{rtd}	kW	0.14	-	-	0.23	-	0.30	-
				Hp	0.19	-	-	0.31	-	0.41	-
400 Vac (560 Vdc)	Rated Torque (speed) ①②⑦⑧		T_{rtd}	Nm	-	-	-	-	-	-	-
				lb-in	-	-	-	-	-	-	-
	Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-
	Rated Power (speed) ①②⑦		P_{rtd}	kW	-	-	-	-	-	-	-
				Hp	-	-	-	-	-	-	-
480 Vac (640 Vdc)	Rated Torque (speed) ①②⑦⑧		T_{rtd}	Nm	-	-	-	-	-	-	-
				lb-in	-	-	-	-	-	-	-
	Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-
	Rated Power (speed) ①②⑦		P_{rtd}	kW	-	-	-	-	-	-	-
				Hp	-	-	-	-	-	-	-

See following page for notes.

AKM1x Motor Parameters

				AKM11			AKM12		AKM13	
Parameters	Tol	Symbol	Units	B	C	E	C	E	C	D
Torque Constant ①	±10%	K_t	Nm/A_{rms}	0.158	0.129	0.064	0.207	0.112	0.278	0.169
			$lb\text{-}in/A_{rms}$	1.40	1.14	0.57	1.83	0.99	2.46	1.50
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	10.2	8.3	4.1	13.3	7.2	17.9	10.9
Motor Constant	Nom	K_m	$N\text{-}m/\sqrt{W}$	0.0302	0.0303	0.0296	0.0480	0.0463	0.0618	0.0593
			$lb\text{-}in/\sqrt{W}$	0.267	0.268	0.262	0.425	0.410	0.547	0.525
Resistance (line-line) ⑥	±10%	R_m	ohm	18.2	12.1	3.11	12.4	3.9	13.5	5.41
Inductance (line-line)		L	mH	12.5	8.3	2.04	9.1	2.7	10.3	3.8
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	0.017			0.031		0.045	
			$lb\text{-}in\text{-}s^2$	1.5E-05			2.7E-05		4.0E-05	
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.0013			0.0013		0.0013	
			$lb\text{-}in\text{-}s^2$	0.12E-05			0.12E-05		0.12E-05	
Weight (w/o brake) ⑨		W	kg	0.35			0.49		0.63	
			lb	0.8			1.1		1.4	
Static Friction ①⑧		T_f	Nm	0.0011			0.0021		0.0031	
			lb-in	0.01			0.02		0.03	
Viscous Damping ①		K_{dv}	Nm/krpm	0.0005			0.001		0.0015	
			lb-in/krpm	0.004			0.009		0.013	
Thermal Time Constant		TCT	minutes	4			6		7	
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	1.83			1.63		1.53	
Operating Ambient Temperature Range ⑪⑫			°C	-20 to 40			-20 to 40		-20 to 40	
Pole Pairs				3			3		3	
Heat Sink Size				10"x10"x1/4" Aluminum Plate			10"x10"x1/4" Aluminum Plate		10"x10"x1/4" Aluminum Plate	

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ For non-resolver feedback options: no continuous torque reduction.
⑧ For motors with optional shaft seal, reduce torque shown by 0.021 Nm (0.19 lb-in), and increase T_f by the same amount.
⑨ Brake option increases weight by 0.19 kg (0.42 lb).
⑩ Motors can be operated up to 240 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑪ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑫ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.


Related Resources:
AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)


AKM1x Series Motor Specifications

AKM1x Frame Dimensional Drawings


AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools

C-, M-, P- connector options







ytec Y- connector option



itec 9- connector option



Shaft-keyway dimensions



Dimensional data tables for callouts are located on the following page.

AKM1x Frame Dimensional Data

AKM1x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"
AK	4.30 [0.169]	30 [1.1811]	46 [1.811]	–	–	8 [0.3150]	25 [0.984]
AN	4.30 [0.169]	30 [1.1811]	46 [1.811]	–	–	8 [0.3150]	25 [0.984]
BN	3.56 [0.140]	20.02 [0.788]	46.69 [1.838]	–	–	6.350 [0.2500]	25 [0.984]
CK	3.40 [0.134]	30 [1.1811]	45 [1.772]	–	–	8 [0.3150]	25 [0.984]
CN	3.40 [0.134]	30 [1.1811]	45 [1.772]	–	–	8 [0.3150]	25 [0.984]

Mounting Flange-Shaft	Shaft Dia. w/ Key "L"	Key Width "M"	Key Length "N"
AK	9.20 [0.362]	3 [0.1181]	14 [0.551]
AN	–	–	–
BN	–	–	–
CK	9.20 [0.362]	3 [0.1181]	14 [0.551]
CN	–	–	–

AKM1x Motor Length Dimensional Data

	No Brake (N)						
	X		Y MAX		Z MAX		
Connector	C-, M-, P-	Y-, 9-	C- M-	Y- 9-	C-, M-, P-		Y-
Feedback Option	R, C-, 1-, 2-, Gx	R-, C-, CA 1-, 2-, Gx	R-	R-, C-, CA-, 1-, 2-	C-, 1-, 2-	Gx	Gx
AKM11	56.1 [2.21]	60.8 [2.39]	69.6 [2.74]	79 [3.11]	79 [3.11]	88.5 [3.48]	
AKM12	75.1 [2.96]	79.8 [3.14]	88.6 [3.49]	98 [3.86]	98 [3.86]	107.5 [4.23]	
AKM13	94.1 [3.7]	98.8 [3.89]	107.6 [4.24]	117 [4.61]	117 [4.61]	126.5 [4.98]	

	Brake (2)						
	X			Y MAX		Z MAX	
Connector	C-, M-, P-	C-, M-	Y-, 9-	C-, M-	Y-, 9-	C-, M-, P-	Y-, 9-
Feedback Option	R-, C-, Gx	1-, 2-	R-, C-, CA 1-, 2-, Gx	R-		C-, 1-, 2-, Gx	C-, CA-, 1-, 2-, Gx
AKM11	96.2 [3.79]	98.2 [3.86]	96.2 [3.79]	115.6 [4.55]		125 [4.92]	
AKM12	115.2 [4.54]	117.2 [4.61]	115.2 [4.54]	134.6 [5.3]		144 [5.67]	
AKM13	134.2 [5.28]	136.2 [5.28]	134.2 [5.28]	153.6 [6.05]		163 [6.42]	

Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:
Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

AKM2x Series Motor Specifications

AKM2x Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM21			AKM22			AKM23				AKM24			
	Parameters	Tol	Symbol	Units	C	E	G	C	E	G	C	D	E	F	C	D	E	F
	Max Rated Voltage ⑫	Max	–	Vac	240	120	–	480	240	120	480	480	400	240	480	480	400	240
				Vdc	320	160	75	640	320	160	640	640	560	320	640	640	560	320
	Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	0.48	0.50	0.50	0.84	0.87	0.88	1.13	1.16	1.16	1.18	1.38	1.41	1.40	1.42
				lb-in	4.2	4.4	4.4	7.4	7.7	7.8	10	10.3	10.3	10.4	12.2	12.5	12.4	12.6
	Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	1.58	3.11	4.87	1.39	2.73	4.82	1.41	2.19	2.78	4.31	1.42	2.21	2.79	3.89
	Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	0.38	0.40	0.40	0.67	0.70	0.70	0.90	0.92	0.93	0.94	1.104	1.13	1.12	1.14
				lb-in	3.4	3.5	3.5	5.9	6.2	6.2	8	8.2	8.23	8.4	9.77	10.0	9.91	10.1
	Max Mechanical Speed ⑤	Nom	N_{max}	rpm	8000	8000	8000	8000	8000	8000	8000	8000	8000	8000	8000	8000	8000	8000
	Peak Torque ①②	Nom	T_p	Nm	1.47	1.50	1.51	2.73	2.78	2.79	3.81	3.84	3.86	3.89	4.73	4.76	4.79	4.82
				lb-in	13.0	13.3	13.4	24.2	24.6	24.7	33.7	34.0	34.2	34.4	41.9	42.1	42.4	42.7
	Peak Current	Nom	I_p	A_{rms}	6.3	12.5	19.5	5.6	11.0	19.3	5.7	8.8	11.1	17.3	5.7	8.8	11.2	15.6
75 Vdc	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	0.48	0.46	-	0.85	0.83	-	-	-	1.15	-	-	-	1.39
				lb-in	-	4.2	4.1	-	7.5	7.4	-	-	-	10.2	-	-	-	12.3
	Rated Speed		N_{rtd}	rpm	-	2000	4000	-	1000	2500	-	-	-	1500	-	-	-	1000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	0.10	0.19	-	0.09	0.22	-	-	-	0.18	-	-	-	0.15
				Hp	-	0.13	0.26	-	0.12	0.29	-	-	-	0.24	-	-	-	0.20
120 Vac (160 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	0.46	0.41	-	0.83	0.81	0.74	1.11	1.12	1.1	1.07	-	1.36	1.34	1.33
				lb-in	4.0	3.7	-	7.3	7.1	6.5	9.8	9.9	9.7	9.5	-	12.0	11.9	11.8
	Rated Speed		N_{rtd}	rpm	2500	7000	-	1000	3500	7000	1000	1500	2500	4500	-	1500	2000	3000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.12	0.30	-	0.09	0.30	0.54	0.12	0.18	0.29	0.50	-	0.21	0.28	0.42
				Hp	0.16	0.41	-	0.12	0.40	0.72	0.16	0.24	0.39	0.68	-	0.29	0.38	0.56
240 Vac (320 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	0.39	-	-	0.78	.70	-	1.08	1.03	0.98	0.94	1.32	1.29	1.24	1.12
				lb-in	3.4	-	-	6.9	6.2	-	9.6	9.1	8.7	8.3	11.7	11.4	11.0	9.9
	Rated Speed		N_{rtd}	rpm	8000	-	-	3500	8000	-	2500	5000	6500	8000	2000	4000	5500	8000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.32	-	-	0.29	0.59	-	0.28	0.54	0.67	0.79	0.28	0.54	0.71	0.94
				Hp	0.43	-	-	0.38	0.79	-	0.38	0.72	0.89	1.06	0.37	0.72	0.96	1.26
400 Vac (560 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	0.68	-	-	0.99	0.92	0.87	-	1.25	1.11	0.98	-
				lb-in	-	-	-	6.0	-	-	8.8	8.1	7.7	-	11.1	9.8	8.7	-
	Rated Speed		N_{rtd}	rpm	-	-	-	8000	-	-	5500	8000	8000	-	4500	8000	8000	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	0.57	-	-	0.57	0.77	0.73	-	0.59	0.93	0.82	-
				Hp	-	-	-	0.76	-	-	0.76	1.03	0.98	-	0.79	1.25	1.1	-
480 Vac (640 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	0.68	-	-	0.95	0.92	-	-	1.22	1.11	-	-
				lb-in	-	-	-	6.0	-	-	8.4	8.1	-	-	10.8	9.8	-	-
	Rated Speed		N_{rtd}	rpm	-	-	-	8000	-	-	7000	8000	-	-	5500	8000	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	0.57	-	-	0.7	0.77	-	-	0.94	0.93	-	-
				Hp	-	-	-	0.76	-	-	0.93	1.03	-	-	0.7	1.25	-	-

See following page for notes.

AKM2x Motor Parameters

				AKM21			AKM22			AKM23				AKM24			
Parameters	Tol	Symbol	Units	C	E	G	C	E	G	C	D	E	F	C	D	E	F
Torque Constant ①	±10%	K_t	Nm/A_{rms}	0.30	0.16	0.10	0.61	0.32	0.18	0.8	0.52	0.42	0.27	0.97	0.63	0.50	0.36
			$lb\text{-}in/A_{rms}$	2.7	1.4	0.9	5.4	2.8	1.6	7.1	4.6	3.7	2.4	8.6	5.6	4.4	3.2
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	19.5	10.2	6.6	39	20.4	11.7	51.8	33.8	27.0	17.6	62.4	40.8	32.5	23.4
Motor Constant	Nom	K_m	N-m/√W	0.0679	0.0706	0.0680	0.111	0.114	0.110	0.142	0.143	0.147	0.144	0.175	0.171	0.175	0.171
			lb-in/√W	0.601	0.625	0.602	0.986	1.01	0.98	1.26	1.27	1.30	1.28	1.55	1.52	1.55	1.52
Resistance (line-line) ⑥	±10%	R_m	ohm	13	3.42	1.44	20.0	5.2	1.77	21.2	8.8	5.4	2.34	20.4	9.0	5.4	2.94
Inductance (line-line)		L	mH	19	5.2	2.18	35.5	9.7	3.19	40.7	17.3	11.1	4.68	43.8	18.7	11.8	6.16
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	0.11			0.16			0.22				0.27			
			$lb\text{-}in\text{-}s^2$	9.5E-05			1.4E-04			1.9E-04				2.4E-04			
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.013			0.013			0.013				0.013			
			$lb\text{-}in\text{-}s^2$	1.2E-05			1.2E-05			1.2E-05				1.2E-05			
Weight (w/o brake) ⑪		W	kg	0.82			1.1			1.38				1.66			
			lb	1.8			2.4			3.0				3.7			
Static Friction ①⑩		T_f	Nm	0.002			0.005			0.007				0.01			
			lb-in	0.02			0.04			0.06				0.09			
Viscous Damping ①		K_{dv}	Nm/krpm	0.0046			0.0055			0.0065				0.0074			
			lb-in/krpm	0.04			0.05			0.06				0.07			
Thermal Time Constant		TCT	minutes	8			9			10				11			
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	1.43			1.19			1.10				1.07			
Operating Ambient Temperature Range ⑬⑭⑮			°C	-20 to 40			-20 to 40			-20 to 40				-20 to 40			
Pole Pairs				3			3			3				3			
Heat Sink Size				10"x10"x1/4" Aluminum Plate			10"x10"x1/4" Aluminum Plate			10"x10"x1/4" Aluminum Plate				10"x10"x1/4" Aluminum Plate			

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake option reduces continuous torque ratings by:
AKM21 = 0.00 AKM22 = 0.01 Nm AKM23 = 0.02 Nm AKM24 = 0.05 Nm
⑧ For non-resolver feedback options: no continuous torque reduction.
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM21 = 0.00 AKM22 = 0.02 Nm AKM23 = 0.05 Nm AKM24 = 0.12 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.047 Nm (0.41 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 0.27 kg (0.59 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.

Related Resources:


AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)


AKM2x Series Motor Specifications

AKM2x Frame Dimensional Drawings


AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools


B- connector option






G- connector option







9- connector options





C-, M-, P- connector options





Shaft-keyway dimensions





Dimensional data tables for callouts are located on the following page.

AKM2x Frame Dimensional Data

AKM2x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"	Shaft Dia. w/ Key "L"
AC	4.80 [0.189]	40 [1.5748]	63 [2.480]	74 [2.913]	D M3 DIN 332	9 [0.3543]	20.0 [0.79]	–
AN	4.80 [0.189]	40 [1.5748]	63 [2.480]	74 [2.913]	D M3 DIN 332	9 [0.3543]	20.0 [0.79]	–
BN	5.10 [0.201]	38.10 [1.500]	66.68 [2.625]	–	–	9.525 [0.3750]	31.75[1.250]	–
CK	5.80 [0.228]	50 [1.9685]	70 [2.756]	_	_	14 [0.5512]	30.0 [1.181]	16 [0.630]
DC	5.80 [0.228]	40 [1.5748]	65 [2.559]	_	D M3 DIN 332	9 [0.3543]	20.0 [0.79]	–
DN	5.80 [0.228]	40 [1.5748]	65 [2.559]	–	D M3 DIN 332	9 [0.3543]	20.0 [0.79]	–
EN & EF	5.10 [0.201]	38.10 [1.500]	66.68 [2.625]	–	–	9.525 [0.3750]	20.57 [0.810]	–

Mounting Flange-Shaft	Key Width "M"	Key Length "N"	Shaft Dia. w/ Key "P"	Key Width "R"	"S"	Key Length "T"	"U"	"V"	"W"
AC	–	–	10.2 [0.402]	3 [0.1181]	300 [0.118]	12 [0.472]	0.030 [0.0011]	0.060 [0.0023]	0.060 [0.0023]
AN	–	–	–	–	–	–	0.030 [0.0011]	0.060 [0.0023]	0.060 [0.0023]
BN	–	–	–	–	–	–	0.051 [0.0020]	0.10 [0.004]	0.10 [0.004]
CK	5 [0.197]	20 [0.787]	–	–	–	–	0.035 [0.0013]	0.080 [0.0031]	0.080 [0.0031]
DC	–	–	10.2 [0.402]	3 [0.1181]	300 [0.118]	12 [0.472]	0.030 [0.0011]	0.060 [0.0023]	0.060 [0.0023]
DN	–	–	–	–	–	–	0.030 [0.0011]	0.060 [0.0023]	0.060 [0.0023]
EN & EF	–	–	–	–	–	–	0.051 [0.0020]	0.10 [0.004]	0.10 [0.004]

AKM2x Motor Length Dimensional Data

	No Brake (N)					
	X		Y MAX		Z MAX	
Connector	C-, M-, P-	B-, G-, 9-	C-, M-	B-, G-, 9-	C-, M-, P-	B-, G-, 9-
Feedback Option	R, C-, 1-, 2-, Ex, Ax, Dx, Lx	R, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-	R, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx	C-, 1-, 2-, Ex, Ax, Dx, Lx	Gx
AKM21	74.6 [2.94]	76.1 [3]	86.2 [3.39]	95.4 [3.76]	95.4 [3.76]	113.4 [4.46]
AKM22	93.6 [3.69]	95.1 [3.74]	105.2 [4.14]	114.4 [4.5]	114.4 [4.5]	132.4 [5.21]
AKM23	112.6 [4.43]	114.1 [4.49]	124.2 [4.89]	133.4 [5.25]	133.4 [5.25]	151.4 [5.96]
AKM24	131.6 [5.18]	133.1 [5.24]	143.2 [5.64]	152.4 [6]	152.4 [6]	170.4 [6.71]

	Brake (2)				
	X		Z MAX		
Connector	C-, M-, P-	B-, G-, 9-	C-, M-, P-	B-, G-, 9-	B-, G-, 9-
Feedback Option	R, C-, 1-, 2-, Ex, Ax, Dx, Lx	R, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R, C-, 1-, 2-, Ex, Ax, Dx, Lx	R, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx	Gx
AKM21	74.6 [2.94]	76.1 [3]	129.5 [5.1]		147.1 [5.79]
AKM22	93.6 [3.69]	95.1 [3.74]	148.5 [5.85]		166.1 [6.54]
AKM23	112.6 [4.43]	114.1 [4.49]	167.5 [6.59]		185.1 [7.29]
AKM24	131.6 [5.18]	133.1 [5.24]	186.5 [7.34]		204.1 [8.04]

Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:

Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

AKM3x Series Motor Specifications

AKM3x Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM31			AKM32				AKM33		
	Parameters	Tol	Symbol	Units	C	E	H	C	D	E	H	C	E	H
	Max Rated Voltage ⑫	Max	–	Vac	480	240	120	480	480	480	240	480	480	240
				Vdc	640	320	160	640	640	640	320	640	640	320
	Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	1.15	1.20	1.23	2.00	2.04	2.04	2.10	2.71	2.79	2.88
				lb-in	10.2	10.6	10.8	17.7	18.1	18.1	18.6	24.0	24.7	25.5
	Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	1.37	2.99	5.85	1.44	2.23	2.82	5.50	1.47	2.58	5.62
	Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	0.92	0.96	0.98	1.60	1.63	1.63	1.68	2.17	2.23	2.30
				lb-in	8.1	8.5	8.7	14.2	14.4	14.4	14.9	19.2	19.7	20.4
	Max Mechanical Speed ⑤	Nom	N_{max}	rpm	8000	8000	8000	8000	8000	8000	8000	8000	8000	8000
	Peak Torque ①②	Nom	T_p	Nm	3.88	4.00	4.06	6.92	7.10	7.11	7.26	9.76	10.0	10.2
				lb-in	34.3	35.4	35.9	61.2	62.8	62.9	64.3	86.4	88.1	90.4
	Peak Current	Nom	I_p	A_{rms}	5.5	12.0	23.4	5.7	8.9	11.3	22.0	5.9	10.3	22.5
75 Vdc	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	1.19	1.20	-	-	-	2.06	-	-	2.82
				lb-in	-	10.5	10.6	-	-	-	18.2	-	-	24.6
	Rated Speed		N_{rtd}	rpm	-	750	2000	-	-	-	1200	-	-	800
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	0.09	0.25	-	-	-	0.26	-	-	0.24
				Hp	-	0.13	0.34	-	-	-	0.35	-	-	0.32
120 Vac (160 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	1.17	0.97	-	2.00	2.01	1.96	-	-	2.66
				lb-in	-	10.3	8.6	-	17.7	17.7	17.4	-	-	23.5
	Rated Speed		N_{rtd}	rpm	-	2500	6000	-	1000	1000	3000	-	-	2500
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	0.31	0.61	-	0.21	0.21	0.62	-	-	0.70
				Hp	-	0.41	0.82	-	0.28	0.28	0.83	-	-	0.93
240 Vac (320 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	1.12	0.95	-	1.95	1.93	1.87	1.45	2.64	2.62	2.27
				lb-in	9.9	8.4	-	17.3	17.1	16.5	12.8	23.4	23.2	20.1
	Rated Speed		N_{rtd}	rpm	2500	6000	-	1500	2500	3500	7000	1000	2000	5500
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.29	0.60	-	0.31	0.51	0.69	1.06	0.28	0.55	1.31
				Hp	0.39	0.80	-	0.41	0.68	0.93	1.42	0.37	0.74	1.75
400 Vac (560 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	1.00	-	-	1.86	1.65	1.41	-	2.54	2.34	-
				lb-in	8.9	-	-	16.5	14.6	12.5	-	22.5	20.7	-
	Rated Speed		N_{rtd}	rpm	5000	-	-	3000	5500	7000	-	2000	4500	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.52	-	-	0.58	0.95	1.03	-	0.53	1.10	-
				Hp	0.70	-	-	0.78	1.27	1.38	-	0.71	1.48	-
480 Vac (640 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	0.91	-	-	1.83	1.58	1.22	-	2.50	2.27	-
				lb-in	8.1	-	-	16.2	14.0	10.8	-	22.1	20.1	-
	Rated Speed		N_{rtd}	rpm	6000	-	-	3500	6000	8000	-	2500	5000	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.57	-	-	0.67	0.99	1.02	-	0.65	1.19	-
				Hp	0.77	-	-	0.90	1.33	1.37	-	0.88	1.59	-

See following page for notes.

AKM3x Motor Parameters

				AKM31			AKM32				AKM33		
Parameters	Tol	Symbol	Units	C	E	H	C	D	E	H	C	E	H
Torque Constant ①	±10%	K_t	Nm/A_{rms}	0.85	0.41	0.21	1.40	0.92	0.73	0.39	1.86	1.10	0.52
			$lb\text{-}in/A_{rms}$	7.5	3.6	1.9	12.4	8.1	6.5	3.5	16.5	9.7	4.6
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	54.5	26.1	13.7	89.8	59.0	47.1	24.8	120	70.6	33.4
Motor Constant	Nom	K_m	N-m/√W	0.150	0.154	0.151	0.235	0.232	0.237	0.245	0.295	0.299	0.303
			lb-in/√W	1.33	1.36	1.34	2.08	2.05	2.10	2.17	2.61	2.65	2.68
Resistance (line-line) ⑥	±10%	R_m	ohm	21.4	4.74	1.29	23.8	9.7	6.3	1.69	26.6	9.0	1.96
Inductance (line-line)		L	mH	37.5	8.6	2.4	46.5	20.1	12.8	3.5	53.6	18.5	4.1
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	0.33			0.59				0.85		
			$lb\text{-}in\text{-}s^2$	2.9E-04			5.2E-04				7.5E-04		
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.014			0.014				0.014		
			$lb\text{-}in\text{-}s^2$	1.2E-05			1.2E-05				1.2E-05		
Weight (w/o brake) ⑪		W	kg	1.55			2.23				2.9		
			lb	3.4			4.9				6.4		
Static Friction ①⑩		T_f	Nm	0.014			0.02				0.026		
			lb-in	0.12			0.18				0.23		
Viscous Damping ①		K_{dv}	Nm/krpm	0.002			0.003				0.004		
			lb-in/krpm	0.02			0.03				0.04		
Thermal Time Constant		TCT	minutes	14			17				20		
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	1.11			0.92				0.78		
Operating Ambient Temperature Range ⑬ ⑭ ⑮			°C	-20 to 40			-20 to 40				-20 to 40		
Pole Pairs				4			4				4		
Heat Sink Size				10"x10"x1/4" Aluminum Plate			10"x10"x1/4" Aluminum Plate				10"x10"x1/4" Aluminum Plate		

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake option reduces continuous torque ratings by:
AKM31 = 0.0 Nm AKM32 = 0.05 Nm AKM33 = 0.1 Nm
⑧ For non-resolver feedback options: no continuous torque reduction.
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM31 = 0.0 Nm AKM32 = 0.1 Nm AKM33 = 0.2 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.047 Nm (0.41 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 0.36 kg (0.79 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.


Related Resources:
AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)

AKM3x Series Motor Specifications


AKM3x Frame Dimensional Drawings

AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools


C- connector option




G- connector option




9- connector option



M-, P- connector options



Shaft-keyway dimensions



Dimensional data tables for callouts are located on the following page.

AKM3x Frame Dimensional Data

AKM3x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"	Shaft Dia. w/ Key "P"
AC	5.80 [0.228]	60 [2.3622]	75 [2.953]	90 [3.543]	D M5 DIN 332	14 [0.5512]	30.0 [1.181]	16 [0.630]
AN	5.80 [0.228]	60 [2.3622]	75 [2.953]	90 [3.543]	D M5 DIN 332	14 [0.5512]	30.0 [1.181]	–
CC	5.80 [0.228]	60 [2.3622]	85 [3.346]	–	D M5 DIN 332	14 [0.5512]	30.0 [1.181]	16 [0.630]
CN	5.80 [0.228]	60 [2.3622]	85 [3.346]	–	D M5 DIN 332	14 [0.5512]	30.0 [1.181]	–
GC	5.80 [0.228]	60 [2.3622]	75 [2.953]	90 [3.543]	D M5 DIN 332	11[0.4331]	23 [0.906]	12.5 [0.492]
GN	5.80 [0.228]	60 [2.3622]	75 [2.953]	90 [3.543]	D M5 DIN 332	11 [0.4331]	23 [0.906]	–

Mounting Flange-Shaft	Key Width "R"	"S"	Key Length "T"	"U"	"V"	"W"
AC	5 [0.197]	5.00 [1.97]	20 [0.787]	0.035 [0.0013]	0.080 [0.0031]	0.080 [0.0031]
AN	–	–	–	0.035 [0.0013]	0.080 [0.0031]	0.080 [0.0031]
CC	5 [0.197]	5.00 [1.97]	20 [0.787]	0.035 [0.0013]	0.080 [0.0031]	0.080 [0.0031]
CN	–	–	–	0.035 [0.0013]	0.080 [0.0031]	0.080 [0.0031]
GC	4 [0.157]	3.5 [0.138]	16 [0.630]	0.035 [0.0013]	0.080 [0.0031]	0.080 [0.0031]
GN	–	–	–	0.035 [0.0013]	0.080 [0.0031]	0.080 [0.0031]

AKM3x Motor Length Dimensional Data

	No Brake (N)		
	X*	Y MAX	Z MAX
Connector	C-, 9-, G-, M-, P-	C-, 9-, G-, M-, P-	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx	Gx
AKM31	87.9 [3.46]	109.8 [4.32]	125.3 [4.93]
AKM32	118.9 [4.68]	140.8 [5.54]	156.3 [6.15]
AKM33	149.9 [5.9]	171.8 [6.76]	187.3 [7.37]

	Brake (2)		
	X*	Z MAX	
Connector	C-, 9-, G-, M-, P-	C-, 9-, G-, M-, P-	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx	Gx
AKM31	87.9 [3.46]	141.3 [5.56]	159.3 [6.27]
AKM32	118.9 [4.68]	172.3 [6.78]	190.3 [7.49]
AKM33	149.9 [5.9]	203.3 [8]	221.3 [8.71]

*For 0.5m shielded cable option (M or P), add 6.7 mm to "X"
Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:
Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

AKM4x Series Motor Specifications

AKM41-42 Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM41			AKM42				
	Parameters	Tol	Sym	Units	C	E	H	C	E	G	H	J
	Max Rated Voltage ⑫	Max	–	Vac	480	480	240	480	480	480	240	240
				Vdc	640	640	320	640	640	640	320	320
	Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	1.95	2.02	2.06	3.35	3.42	3.53	3.54	3.56
				lb-in	17.3	17.9	18.2	29.6	30.3	31.2	31.3	31.5
	Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	1.46	2.85	5.60	1.40	2.74	4.8	5.9	8.4
	Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	1.56	1.62	1.65	2.68	2.74	2.82	2.83	2.85
				lb-in	13.8	14.3	14.6	23.7	24.2	25	25	25.2
	Max Mechanical Speed ⑤	Nom	N_{max}	rpm	6000	6000	6000	6000	6000	6000	6000	6000
	Peak Torque ①②	Nom	T_p	Nm	6.1	6.3	6.4	11.1	11.3	11.5	11.6	11.6
				lb-in	54.2	55.6	56.3	98.2	99.7	102	103	103
	Peak Current	Nom	I_p	A_{rms}	5.8	11.4	22.4	5.60	11.0	19.2	24.0	33.7
75 Vdc	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	1.99	-	-	-	-	-
				lb-in	-	-	17.6	-	-	-	-	-
	Rated Speed		N_{rtd}	rpm	-	-	1000	-	-	-	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	0.21	-	-	-	-	-
				Hp	-	-	0.28	-	-	-	-	-
120 Vac (160 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	1.94	1.86	-	-	-	3.2	3.03
				lb-in	-	17.2	16.5	-	-	-	28.3	26.8
	Rated Speed		N_{rtd}	rpm	-	1200	3000	-	-	-	2000	3000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	0.24	0.58	-	-	-	0.67	0.95
				Hp	-	0.33	0.78	-	-	-	0.9	1.28
240 Vac (320 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	1.88	1.82	1.62	-	3.12	2.90	2.72	2.38
				lb-in	16.6	16.1	14.3	-	27.6	25.7	24.1	21.1
	Rated Speed		N_{rtd}	rpm	1200	3000	6000	-	1800	3500	4500	6000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.24	0.57	1.02	-	0.59	1.06	1.28	1.50
				Hp	0.32	0.77	1.36	-	0.79	1.42	1.72	2.00
400 Vac (560 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	1.77	1.58	-	3.10	2.81	2.35	-	-
				lb-in	15.7	14.0	-	27.4	24.9	20.8	-	-
	Rated Speed		N_{rtd}	rpm	3000	6000	-	1500	3500	6000	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.56	0.99	-	0.49	1.03	1.48	-	-
				Hp	0.75	1.33	-	0.65	1.38	1.98	-	-
480 Vac (640 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	1.74	1.58	-	3.02	2.72	2.35	-	-
				lb-in	15.4	14.0	-	26.7	24.1	20.8	-	-
	Rated Speed		N_{rtd}	rpm	3500	6000	-	2000	4000	6000	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.64	0.99	-	0.63	1.14	1.48	-	-
				Hp	0.85	1.33	-	0.85	1.53	1.98	-	-

See following page for notes.

AKM41-42 Motor Parameters

				AKM41			AKM42				
Parameters	Tol	Sym	Units	C	E	H	C	E	G	H	J
Torque Constant ①	±10%	K_t	Nm/A_{rms}	1.34	0.71	0.37	2.39	1.26	0.74	0.59	0.43
			$lb\text{-}in/A_{rms}$	11.9	6.3	3.3	21.2	11.2	6.5	5.2	3.8
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	86.3	45.6	23.7	154	80.9	47.5	38.3	27.5
Motor Constant	Nom	K_m	N-m/√W	0.237	0.236	0.242	0.374	0.369	0.381	0.375	0.393
			lb-in/√W	2.10	2.09	2.14	3.31	3.26	3.37	3.31	3.47
Resistance (line-line) ⑥	±10%	R_m	ohm	21.3	6.0	1.56	27.5	7.5	2.51	1.65	0.8
Inductance (line-line)		L	mH	66.1	18.4	5.0	97.4	26.8	9.2	6	3.1
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	0.81			1.5				
			$lb\text{-}in\text{-}s^2$	7.2E-04			1.3E-03				
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.058			0.058				
			$lb\text{-}in\text{-}s^2$	5.1E-05			5.1E-05				
Weight (w/o brake) ⑪		W	kg	2.44			3.39				
			lb	5.4			7.5				
Static Friction ①⑩		T_f	Nm	0.014			0.026				
			lb-in	0.12			0.23				
Viscous Damping ①		K_{dv}	Nm/krpm	0.009			0.013				
			lb-in/krpm	0.08			0.12				
Thermal Time Constant		TCT	minutes	13			17				
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	0.97			0.80				
Operating Ambient Temperature Range ⑬⑭⑮			°C	-20 to 40			-20 to 40				
Pole Pairs				5			5				
Heat Sink Size				10"x10"x1/4" Aluminum Plate			10"x10"x1/4" Aluminum Plate				

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake motor option reduces continuous torque ratings by 0.12 Nm.
⑧ Non-Resolver feedback options reduces continuous ratings by:
AKM41 = 0.1 Nm AKM42 = 0.1 Nm AKM43 = 0.2 Nm AKM44 = 0.3 Nm
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM41 = 0.22 Nm AKM42 = 0.36 Nm AKM43 = 0.55 Nm AKM44 = 0.76 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.071 Nm (0.63 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 0.69 kg (1.52 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.
⑯ High speed continuous performance could be reduced by additional losses due to combination of source voltage, winding inductance, and servo drive PWM frequency. Please contact Kollmorgen Customer Support with your specific applications requirements.

Related Resources:

AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)

AKM4x Series Motor Specifications

AKM43-44 Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM43					AKM44				
	Parameters	Tol	Sym	Units	E	G	H	K	L	E	G	H	J	K
	Max Rated Voltage ⑫	Max	–	Vac	480	480	400	240	240	480	480	480	480	240
				Vdc	640	640	560	320	320	640	640	640	640	320
	Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	4.70	4.80	4.82	4.90	4.73	5.76	5.88	5.89	6.00	5.88
				lb-in	41.6	42.5	42.7	43.4	41.9	51.0	52	52.1	53.1	52
	Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	2.76	4.87	5.4	9.6	11.2	2.9	5.0	5.6	8.8	10.1
	Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	3.76	3.84	3.86	3.92	3.78	4.61	4.7	4.71	4.80	4.7
				lb-in	33.3	34	34.2	34.7	33.5	40.8	41.6	41.7	42.5	41.6
	Max Mechanical Speed ⑤	Nom	N_{max}	rpm	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
	Peak Torque ①②	Nom	T_p	Nm	15.9	16.1	16.1	16.4	16.0	19.9	23.3	20.2	20.5	20.2
				lb-in	141	142	142	145	142	176	180	179	181	179
	Peak Current	Nom	I_p	A_{rms}	11.0	19.5	21.6	38.4	44.6	11.4	20.0	22.4	35.2	40.4
75 Vdc	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-	-
				lb-in	-	-	-	-	-	-	-	-	-	-
	Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-	-
				Hp	-	-	-	-	-	-	-	-	-	-
120 Vac (160 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	4.08	3.78	-	-	-	-	4.9
				lb-in	-	-	-	36.1	33.5	-	-	-	-	43.4
	Rated Speed		N_{rtd}	rpm	-	-	-	2500	3000	-	-	-	-	2000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	1.07	1.19	-	-	-	-	1.38
				Hp	-	-	-	1.43	1.59	-	-	-	-	1.03
240 Vac (320 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	4.24	4	3.86	2.62	2.53	5.22	4.9	4.66	3.84	3.18
				lb-in	37.5	35.4	34.2	23.2	22.4	46.2	43.4	41.2	34.0	28.1
	Rated Speed		N_{rtd}	rpm	1500	2500	3000	6000	6000	1200	2000	2500	4000	5000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.67	1.05	1.21	1.65	1.59	0.66	1.03	1.22	1.61	1.67
				Hp	0.89	1.4	1.63	2.21	2.13	0.88	1.38	1.64	2.16	2.23
400 Vac (560 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	3.92	3.01	2.81	-	-	4.80	3.76	3.19	2.75	-
				lb-in	34.7	26.6	24.9	-	-	42.5	33.3	28.2	24.3	-
	Rated Speed		N_{rtd}	rpm	2500	5000	5500	-	-	2000	4000	5000	6000	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	1.03	1.58	1.62	-	-	1.01	1.57	1.67	1.73	-
				Hp	1.38	2.11	2.17	-	-	1.35	2.11	2.24	2.32	-
480 Vac (640 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	3.76	2.57	-	-	-	4.56	3.19	2.7	2.75⑯	-
				lb-in	33.3	22.7	-	-	-	40.4	28.2	23.9	24.3⑯	-
	Rated Speed		N_{rtd}	rpm	3000	6000	-	-	-	2500	5000	6000	6000⑯	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	1.18	1.61	-	-	-	1.19	1.67	1.70	1.73⑯	-
				Hp	1.58	2.16	-	-	-	1.60	2.24	2.28	2.32⑯	-

See following page for notes.

AKM43-44 Motor Parameters

				AKM43					AKM44				
Parameters	Tol	Sym	Units	E	G	H	K	L	E	G	H	J	K
Torque Constant ①	±10%	K_t	Nm/A_{rms}	1.72	0.99	0.89	0.52	0.43	2.04	1.20	1.06	0.69	0.59
			$lb\text{-}in/A_{rms}$	15.2	8.8	7.9	4.6	3.8	18.1	10.6	9.4	6.1	5.2
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	111	63.9	57.4	33.2	27.5	132	77	68	44.2	37.8
Motor Constant	Nom	K_m	$N\text{-}m/\sqrt{W}$	0.479	0.482	0.501	0.494	0.465	0.567	0.567	0.580	0.581	0.567
			$lb\text{-}in/\sqrt{W}$	4.24	4.29	4.44	4.37	4.12	5.01	5.03	5.13	5.14	5.10
Resistance (line-line) ⑥	±10%	R_m	ohm	8.61	2.81	2.20	0.74	0.57	8.64	2.80	2.23	0.94	0.68
Inductance (line-line)		L	mH	32.6	10.8	8.8	2.90	2.00	33.9	11.5	9.1	3.8	2.8
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	2.1					2.7				
			$lb\text{-}in\text{-}s^2$	1.8E-03					2.4E-03				
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.058					0.058				
			$lb\text{-}in\text{-}s^2$	5.1E-05					5.1E-05				
Weight (w/o brake) ⑪		W	kg	4.35					5.3				
			lb	9.6					11.7				
Static Friction ①⑩		T_f	Nm	0.038					0.05				
			lb-in	0.34					0.44				
Viscous Damping ①		K_{dv}	Nm/krpm	0.017					0.021				
			lb-in/krpm	0.15					0.19				
Thermal Time Constant		TCT	minutes	20					24				
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	0.70					0.65				
Operating Ambient Temperature Range ⑬ ⑭ ⑮			°C	-20 to 40					-20 to 40				
Pole Pairs				5					5				
Heat Sink Size				10"x10"x1/4" Aluminum Plate					10"x10"x1/4" Aluminum Plate				

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake motor option reduces continuous torque ratings by 0.12 Nm.
⑧ Non-Resolver feedback options reduces continuous ratings by:
AKM41 = 0.1 Nm AKM42 = 0.1 Nm AKM43 = 0.2 Nm AKM44 = 0.3 Nm
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM41 = 0.22 Nm AKM42 = 0.36 Nm AKM43 = 0.55 Nm AKM44 = 0.76 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.071 Nm (0.63 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 0.69 kg (1.52 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.
⑯ High speed continuous performance could be reduced by additional losses due to combination of source voltage, winding inductance, and servo drive PWM frequency. Please contact Kollmorgen Customer Support with your specific applications requirements.

Related Resources:


AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)


AKM4x Series Motor Specifications

AKM4x Frame Dimensional Drawings


AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools

C- connector option







G- connector option




SHOWN WITH "C" CONNECTOR OPTION




9- connector options



M-, P- connector options



Shaft-keyway dimensions



Dimensional data tables for callouts are located on the following page.

AKM4x Frame Dimensional Data

AKM4x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"	Shaft Dia. w/ Key "L"
AC	7 [0.276]	80 [3.1496]	100 [3.937]	–	D M5 DIN 332	19 [0.7480]	40.0 [1.57]	–
AN	7 0[0.276]	80 [3.1496]	100 [3.937]	–	D M5 DIN 332	19 [0.7480]	40.0 [1.57]	–
BK	5.54 [0.218]	73.025 [2.8750]	98.43 [3.875]	–	–	15.875 [0.6250]	52.40 [2.063]	17.92 [0.706]
CC	5.54 [0.218]	60 [2.3622]	90 [3.543]	109 [4.291]	D M5 DIN 332	19 [0.7480]	40.0 [1.57]	–
CN	5.54 [0.218]	60 [2.3622]	90 [3.543]	109 [4.291]	D M5 DIN 332	19 [0.7480]	40.0 [1.57]	–
EK	5.54 [0.218]	73.025 [2.8750]	98.43 [3.875]	–	–	12.7 [0.5000]	31.75 [1.250]	14.09 [0.555]
GC	7 [0.276]	80 [3.1496]	100 [3.937]	–	D M5 DIN 332	14 [0.5512]	30 [1.18]	–
GN	7 [0.276]	80 [3.1496]	100 [3.937]	–	D M5 DIN 332	14 [0.5512]	30 [1.18]	–
HC	5.54 [0.218]	60 [2.3622]	90 [3.543]	109 [4.291]	D M5 DIN 332	14 [0.5512]	30 [1.18]	–
HN	5.54 [0.218]	60 [2.3622]	90 [3.543]	109 [4.291]	D M5 DIN 332	14 [0.5512]	30 [1.18]	–
KK	7 [0.276]	70 [2.7559]	90 [3.543]	109 [4.291]	–	16 [0.6299]	40.0 [1.57]	–

Mounting Flange-Shaft	Key Width "M"	Key Length "N"	Shaft Dia. w/ Key "P"	Key Width "R"	"S"	Key Length "T"	"U"	"V"	"W"
AC	–	–	21.5 [0.846]	6 [0.236]	4.00 [1.57]	32 [1.260]	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
AN	–	–	–	–	–	–	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
BK	4.762 [0.1875]	34.93 [1.375]	–	–	–	–	0.051 [0.0020]	0.10 [0.004]	0.10 [0.004]
CC	–	–	21.5 [0.846]	6 [0.236]	4.00 [1.57]	32 [1.260]	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
CN	–	–	–	–	–	–	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
EK	3.175 [0.1250]	19.05 [0.750]	–	–	–	–	0.051 [0.0020]	0.10 [0.004]	0.10 [0.004]
GC	–	–	16 [0.630]	5 [0.197]	6.00 [0.236]	20 [0.787]	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
GN	–	–	–	–	–	–	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
HC	–	–	16 [0.630]	5 [0.197]	6.00 [0.236]	20 [0.787]	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
HN	–	–	–	–	–	–	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
KK	5 [0.197]	30 [1.811]	–	–	–	–	0.051 [0.0020]	0.008 [0.0031]	0.008 [0.0031]

AKM4x Motor Length Dimensional Data

	No Brake (N)		
	X*	Y MAX	Z MAX
Connector	C-, 9-, G, M, P	C-, 9-, G, M, P	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx	Gx
AKM41	96.4 [3.8]	118.8 [4.68]	136.8 [5.39]
AKM42	125.4 [4.94]	147.8 [5.82]	165.8 [6.53]
AKM43	154.4 [6.08]	176.8 [6.96]	194.8 [7.67]
AKM44	183.4 [7.22]	205.8 [8.1]	223.8 [8.81]

	Brake (2)		
	X*	Z MAX	
Connector	C-, 9-, G, M, P	C-, 9-, G, M, P	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx	Gx
AKM41	96.4 [3.8]	152.3 [6]	170.3 [6.7]
AKM42	125.4 [4.94]	181.3 [7.14]	199.3 [7.85]
AKM43	154.4 [6.08]	210.3 [8.28]	228.3 [8.99]
AKM43	183.4 [7.22]	239.3 [9.42]	257.3 [10.13]

*For 0.5m shielded cable option (M or P), add 6.7 mm to "X"

Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:

Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

AKM5x Series Motor Specifications

AKM51-52 Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM51					AKM52					
Parameters	Tol	Sym	Units	E	G	H	K	L	E	G	H	K	L	M
Max Rated Voltage ⑫	Max	–	Vac	480	480	480	240	240	480	480	480	480	480	240
			Vdc	640	640	640	320	320	640	640	640	640	640	320
Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	4.70	4.75	4.79	4.9	4.89	8.34	8.43	8.48	8.6	8.67	8.60
			lb-in	41.6	42	42.4	43.4	43.3	73.8	74.6	75.1	76.1	76.7	76.1
Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	2.75	4.84	6.0	9.4	11.9	2.99	4.72	5.9	9.3	11.6	13.1
Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	3.76	3.8	3.83	3.92	3.91	6.67	6.74	6.78	6.88	6.94	6.88
			lb-in	33.3	33.6	33.9	34.7	34.6	59.0	59.7	60.0	61	61.4	61.0
Max Mechanical Speed ⑤	Nom	N_{max}	rpm	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
Peak Torque ①②	Nom	T_p	Nm	11.6	11.7	11.7	11.9	12.0	21.3	21.4	21.6	21.9	22.0	21.9
			lb-in	103	104	104	105	106	189	189	191	194	195	194
Peak Current	Nom	I_p	A_{rms}	8.2	14.5	18.0	28.2	35.7	9.00	14.1	17.7	27.9	34.8	39.4
75 Vdc															
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-	-	-
Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-	-	-	-	-
120 Vac (160 Vdc)															
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	4.15	3.95	-	-	-	-	-	7.5
			lb-in	-	-	-	36.7	35.0	-	-	-	-	-	66
Rated Speed		N_{rtd}	rpm	-	-	-	2500	3000	-	-	-	-	-	2000
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	1.09	1.24	-	-	-	-	-	1.57
			Hp	-	-	-	1.46	1.66	-	-	-	-	-	2.11
240 Vac (320 Vdc)															
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	4.41	4.02	3.87	2.35	2.00	-	7.69	7.53	6.8	6.40	5.20
			lb-in	39.0	35.6	34.3	20.8	17.7	-	68.1	66.6	60.2	56.6	46.0
Rated Speed		N_{rtd}	rpm	1200	2500	3000	5500	6000	-	1500	1800	3000	3500	4500
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	0.55	1.05	1.22	1.35	1.26	-	1.21	1.42	2.14	2.35	2.45
			Hp	0.74	1.41	1.63	1.81	1.69	-	1.62	1.90	2.86	3.15	3.28
400 Vac (560 Vdc)															
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	3.98	2.62	1.95	-	-	7.61	7.06	6.26	3.9	3.27⑯	-
			lb-in	35.2	23.2	17.3	-	-	67.3	62.5	55.4	34.5	2.89⑯	-
Rated Speed		N_{rtd}	rpm	2500	5000	6000	-	-	1500	2500	3500	5500	6000⑯	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	1.04	1.37	1.22	-	-	1.20	1.85	2.30	2.25	2.06⑯	-
			Hp	1.40	1.84	1.64	-	-	1.60	2.48	3.08	3.01	2.76⑯	-
480 Vac (640 Vdc)															
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	3.80	1.94	1.95	-	-	7.3	6.66	5.77	3.25	-	-
			lb-in	33.6	17.2	17.3	-	-	65	58.9	51.1	28.7	-	-
Rated Speed		N_{rtd}	rpm	3000	6000	6000	-	-	2000	3000	4000	6000	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	1.19	1.22	1.23	-	-	1.53	2.09	2.42	2.04	-	-
			Hp	1.60	1.63	1.65	-	-	2.05	2.8	3.24	2.74	-	-

See following page for notes.

AKM51-52 Motor Parameters

				AKM51					AKM52					
Parameters	Tol	Sym	Units	E	G	H	K	L	E	G	H	K	L	M
Torque Constant ①	±10%	K_t	Nm/A_{rms}	1.71	0.99	0.79	0.52	0.41	2.78	1.79	1.44	0.93	0.75	0.66
			$lb\text{-}in/A_{rms}$	15.2	8.8	7.0	4.6	3.63	24.6	15.8	12.7	8.2	6.6	5.8
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	110	63.6	51.3	33.5	26.6	179	115	92.7	60.1	48.3	42.4
Motor Constant	Nom	K_m	$N\text{-}m/\sqrt{W}$	0.469	0.477	0.465	0.49	0.447	0.761	0.760	0.767	0.775	0.784	0.770
			$lb\text{-}in/\sqrt{W}$	4.15	4.24	4.12	4.35	3.96	6.73	6.71	6.79	6.83	6.94	6.81
Resistance (line-line) ⑥	±10%	R_m	ohm	9.0	2.87	1.85	0.75	0.49	9.0	3.7	2.35	0.96	0.61	0.49
Inductance (line-line)		L	mH	36.6	12.1	7.9	3.38	2.13	44.7	18.5	11.9	5	3.24	2.5
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	3.4					6.2					
			$lb\text{-}in\text{-}s^2$	3.0E-03					5.5E-03					
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.166					0.166					
			$lb\text{-}in\text{-}s^2$	1.47E-04					1.47E-04					
Weight (w/o brake) ⑪		W	kg	4.2					5.8					
			lb	9.3					12.8					
Static Friction ①⑩		T_f	Nm	0.022					0.04					
			lb-in	0.19					0.35					
Viscous Damping ①		K_{dv}	Nm/krpm	0.033					0.042					
			lb-in/krpm	0.29					0.37					
Thermal Time Constant		TCT	minutes	20					24					
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	0.68					0.56					
Operating Ambient Temperature Range ⑬ ⑭ ⑮			°C	-20 to 40					-20 to 40					
Pole Pairs				5					5					
Heat Sink Size				12″x12″x1/2″ Aluminum Plate					12″x12″x1/2″ Aluminum Plate					

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake option reduces continuous torque ratings by:
AKM51 = 0.15 Nm AKM52 = 0.26 Nm AKM53 = 0.35 Nm AKM54 = 0.43 Nm
⑧ Non-Resolver feedback options reduce continuous torque ratings by:
AKM51 = 0.15 Nm AKM52 = 0.34 Nm AKM53 = 0.58 Nm AKM54 = 0.86 Nm
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM51 = 0.39 Nm AKM52 = 0.76 Nm AKM53 = 1.13 Nm AKM54 = 1.55 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.13 Nm (1.2 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 1.2 kg (2.64 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.
⑯ High speed continuous performance could be reduced by additional losses due to combination of source voltage, winding inductance, and servo drive PWM frequency. Please contact Kollmorgen Customer Support with your specific applications requirements.

Related Resources:

AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)

AKM5x Series Motor Specifications

AKM53-54 Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM53							AKM54					
Parameters	Tol	Sym	Units	G	H	K	L	M	P	Q	G	H	K	L	N	P
Max Rated Voltage ⑫	Max	–	Vac	480	480	480	480	240	240	240	480	480	480	400	240	240
			Vdc	640	640	640	640	320	320	320	640	640	640	560	320	320
Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	11.4	11.5	11.6	11.6	11.4	11.4	11.6	14.3	14.2	14.4	14.1	14.1	14.4
			lb-in	101	102	102.7	103	101	101	103	127	126	127	125	125	127
Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	4.77	6.6	9.4	11.8	13.4	19.1	21.1	5	5.5	9.7	12.5	17.8	19.6
Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	9.10	9.21	9.28	9.28	9.10	9.10	9.26	11.41	11.5	11.5	11.3	11.3	11.49
			lb-in	80.5	81.5	82.1	82.1	80.5	80.5	82	101	102	102	100	100	101.7
Max Mechanical Speed ⑤	Nom	N_{max}	rpm	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
Peak Torque ①②	Nom	T_p	Nm	29.9	30.0	30.3	30.3	29.7	29.8	30.2	38.0	37.5	38.4	37.5	37.6	38.0
			lb-in	265	266	268	268	263	264	267	336	332	340	332	333	337
Peak Current	Nom	I_p	A_{rms}	14.4	19.8	28.2	35.4	40.2	57.4	63.3	15.0	16.5	29.1	37.5	53.4	58.8
75 Vdc																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-	-	-	-	-
Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-	-	-	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-	-	-	-	-	-	-
120 Vac (160 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	9.58	-	-	-	-	12.8	12.4
			lb-in	-	-	-	-	-	-	84.8	-	-	-	-	113	110
Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	2500	-	-	-	-	1500	2000
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	2.51	-	-	-	-	2.01	2.6
			Hp	-	-	-	-	-	-	3.36	-	-	-	-	2.7	3.49
240 Vac (320 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	10.7	10.5	10.1	8.9	8.72	5.88	4.99⑯	-	13.4	12.7	11.5	9.85	9.23
			lb-in	94.5	93.0	89.4	79	77.2	52.0	44.2⑯	-	118	112	102	87.2	81.7
Rated Speed		N_{rtd}	rpm	1000	1500	2000	3000	3000	5000	5500⑯	-	1000	1800	2500	3500	4000
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	1.12	1.65	2.12	2.8	2.74	3.08	2.87⑯	-	1.4	2.39	3.00	3.61	3.87
			Hp	1.50	2.21	2.84	3.75	3.67	4.13	3.85⑯	-	1.87	3.20	4.03	4.84	5.18
400 Vac (560 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	9.85	8.83	7.65	5.0⑯	-	-	-	12.92	12.6	10.05	8.13	-	-
			lb-in	87.2	78.2	67.7	44.3⑯	-	-	-	114.3	112	88.9	72.0	-	-
Rated Speed		N_{rtd}	rpm	2000	3000	4000	5500⑯	-	-	-	1500	1800	3500	4500	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	2.06	2.77	3.2	2.88⑯	-	-	-	2.03	2.38	3.68	3.83	-	-
			Hp	2.77	3.72	4.3	3.86⑯	-	-	-	2.72	3.18	4.94	5.14	-	-
480 Vac (640 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	9.50	8.23	6.85	-	-	-	-	12.28	12.2	9.25	-	-	-
			lb-in	84.0	73	60.6	-	-	-	-	108.7	108	81.9	-	-	-
Rated Speed		N_{rtd}	rpm	2400	3500	4500	-	-	-	-	2000	2000	4000	-	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	2.39	3.02	3.23	-	-	-	-	2.57	2.56	3.87	-	-	-
			Hp	3.20	4.05	4.33	-	-	-	-	3.45	3.43	5.19	-	-	-

See following page for notes.

AKM53-54 Motor Parameters

				AKM53							AKM54					
Parameters	Tol	Sym	Units	G	H	K	L	M	P	Q	G	H	K	L	N	P
Torque Constant ①	±10%	K_t	Nm/A_{rms}	2.39	1.74	1.24	0.99	0.85	0.60	0.55	2.87	2.58	1.51	1.13	0.79	0.73
			$lb\text{-}in/A_{rms}$	21.2	15.4	11	8.8	7.5	5.3	4.9	25.4	22.8	13.4	10.0	7.0	6.5
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	154	112	79.8	63.6	54.7	38.4	35.5	185	166	96.6	72.9	51.3	47.3
Motor Constant	Nom	K_m	N-m/√W	0.979	0.986	0.983	0.973	0.972	0.926	0.980	1.164	1.19	1.18	1.14	1.14	1.163
			lb-in/√W	8.67	8.73	8.72	8.61	8.57	8.19	8.76	10.31	10.5	10.4	10.1	10.1	10.21
Resistance (line-line) ⑥	±10%	R_m	ohm	3.97	2.1	1.06	0.69	0.51	0.28	0.21	4.08	3.2	1.08	0.65	0.33	0.27
Inductance (line-line)		L	mH	21.3	11.4	5.7	3.64	2.7	1.3	1.14	22.9	18.3	6.2	3.5	1.75	1.49
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	9.1							12					
			$lb\text{-}in\text{-}s^2$	8.1E-03							0.011					
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.166							0.166					
			$lb\text{-}in\text{-}s^2$	1.47E-04							1.47E-04					
Weight (w/o brake) ⑪		W	kg	7.4							9					
			lb	16.3							19.8					
Static Friction ①⑩		T_f	Nm	0.058							0.077					
			lb-in	0.51							0.68					
Viscous Damping ①		K_{dv}	Nm/krpm	0.052							0.061					
			lb-in/krpm	0.46							0.54					
Thermal Time Constant		TCT	minutes	28							31					
Thermal Resistance		R_{thw-a}	°C/W	0.50							0.45					
Operating Ambient Temperature Range ⑬ ⑭ ⑮			°C	-20 to 40							-20 to 40					
Pole Pairs				5							5					
Heat Sink Size				12″x12″x1/2″ Aluminum Plate							12″x12″x1/2″ Aluminum Plate					

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake option reduces continuous torque ratings by:
AKM51 = 0.15 Nm AKM52 = 0.26 Nm AKM53 = 0.35 Nm AKM54 = 0.43 Nm
⑧ Non-Resolver feedback options reduce continuous torque ratings by:
AKM51 = 0.15 Nm AKM52 = 0.34 Nm AKM53 = 0.58 Nm AKM54 = 0.86 Nm
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM51 = 0.39 Nm AKM52 = 0.76 Nm AKM53 = 1.13 Nm AKM54 = 1.55 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.13 Nm (1.2 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 1.2 kg (2.64 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.
⑯ High speed continuous performance could be reduced by additional losses due to combination of source voltage, winding inductance, and servo drive PWM frequency. Please contact Kollmorgen Customer Support with your specific applications requirements.

Related Resources:


AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)

AKM5x Series Motor Specifications


AKM5x Frame Dimensional Drawings

AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools

C- connector option




G- connector option



9- connector option

Shaft-keyway dimensions



Dimensional data tables for callouts are located on the following page.

AKM5x Frame Dimensional Data

AKM5x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"	Shaft Dia. w/ Key "L"
AC	9 [0.354]	110 [4.3307]	130 [5.118]	–	D M8 DIN 332	24 [0.9449]	50.0 [1.97]	–
AN	9 [0.354]	110 [4.3307]	130 [5.118]	–	D M8 DIN 332	24 [0.9449]	50.0 [1.97]	–
BK	8.33 [0.328]	55.563 [2.1874]	125.73 [4.950]	–	–	19.05 [0.7500]	57.15 [2.250]	21.15 [0.83]
CC	9 [0.354]	95 [3.7402]	115 [4.528]	140 [5.512]	D M8 DIN 332	24 [0.9449]	50.0 [1.97]	–
CN	9 [0.354]	95 [3.7402]	115 [4.528]	140 [5.512]	D M8 DIN 332	24 [0.9449]	50.0 [1.97]	–
DK	8.33 [0.328]	63.5 [2.500]	127 [5.000]	–	–	19.05 [0.7500]	57.15 [2.250]	21.15 [0.83]
EK	8.33 [0.328]	55.563 [2.1874]	125.73 [4.950]	–	–	15.875 [0.6250]	44.45 [1.750]	17.91 [0.705]
GC	9 [0.354]	110 [4.3307]	130 [5.118]	–	D M6 DIN 332	19 [0.7480]	40 [1.57]	–
GN	9 [0.354]	110 [4.3307]	130 [5.118]	–	D M6 DIN 332	19 [0.7480]	40.0 [1.57]	–
HC	9 [0.354]	95 [3.7402]	115 [4.528]	140 [5.512]	D M6 DIN 332	19 [0.7480]	40 [1.57]	–
HN	9 [0.354]	95 [3.7402]	115 [4.528]	140 [5.512]	D M6 DIN 332	19 [0.7480]	40.0 [1.57]	–

Mounting Flange-Shaft	Key Width "M"	Key Length "N"	Shaft Dia. w/ Key "P"	Key Width "R"	"S"	Key Length "T"	"U"	"V"	"W"
AC	–	–	27 [1.063]	8 [0.3150]	5.00 [0.197]	40 [1.575]	0.040 [0.0015]	0.100 [0.0039]	0.100 [0.0039]
AN	–	–	–	–	–	–	0.040 [0.0015]	0.100 [0.0039]	0.100 [0.0039]
BK	4.763 [0.1875	38.1 [1.500]	–	–	–	–	0.051 [0.0020]	0.10 [0.004]	0.10 [0.004]
CC	–	–	27 [1.063]	8 [0.3150]	5.00 [0.197]	40 [1.575]	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
CN	–	–	–	–	–	–	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
DK	4.763 [0.1875	34.93 [1.375]	–	–	–	–	0.051 [0.0020]	0.05 [0.002]	0.10 [0.004]
EK	4.763 [0.1875	38.1 [1.500]	–	–	–	–	0.051 [0.0020]	0.10 [0.004]	0.10 [0.004]
GC	–	–	21.5 [0.846]	6 [0.236]	4.00 [0.157]	32 [1.260]	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
GN	–	–	–	–	–	–	–	–	–
HC	–	–	21.5 [0.846]	6 [0.236]	4.00 [0.157]	32 [1.260]	0.040 [0.0015]	0.080 [0.0031]	0.080 [0.0031]
HN	–	–	–	–	–	–	–	–	–

AKM5x Motor Length Dimensional Data

	No Brake (N)		
	X	Y MAX	Z MAX
Connector	C-, 9-, G	C-, 9-, G	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex	Ax, Dx, Lx, Gx
AKM51	105.3 [4.15]	127.5 [5.02]	146 [5.75]
AKM52	136.3 [5.37]	158.5 [6.24]	177 [6.97]
AKM53	167.3 [6.59]	189.5 [7.46]	208 [8.19]
AKM54	198.3 [7.81]	220.5 [8.68]	239 [9.41]

	Brake (2)		
	X	Z MAX	
Connector	C-, 9-, G	C-, 9-, G	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex	Ax, Dx, Lx, Gx
AKM51	105.3 [4.15]	172.5 [6.79]	189 [7.44]
AKM52	136.3 [5.37]	203.5 [8.01]	220 [8.66]
AKM53	167.3 [6.59]	234.5 [9.23]	251 [9.88]
AKM54	198.3 [7.81]	265.5 [10.45]	282 [11.1]

Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:

Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

AKM6x Series Motor Specifications

AKM62-63 Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM62							AKM63						
Parameters	Tol	Sym	Units	G	H	K	L	M	P	Q	G	H	K	L	M	N	Q
Max Rated Voltage ⑫	Max	–	Vac	480	480	480	480	480	240	240	480	480	480	480	480	480	240
			Vdc	640	640	640	640	640	320	320	640	640	640	640	640	640	320
Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	11.9	11.9	12.2	12.2	12.2	12.3	12.0	16.5	16.6	16.8	16.8	17.0	17	16.7
			lb-in	105	105	108	108	108	109	106	146	147	149	149	150	150	148
Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	4.9	5.4	9.6	12.0	13.4	18.8	21.8	4.5	5.6	9.9	11.1	13.8	17.4	22.4
Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	9.5	9.5	9.8	9.8	9.72	9.8	9.6	13.2	13.3	13.4	13.4	13.6	13.6	13.4
			lb-in	84	84	87	87	86.0	87	85	117	118	119	119	120	120	119
Max Mechanical Speed ⑤	Nom	N_{max}	rpm	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
Peak Torque ①②	Nom	T_p	Nm	29.8	29.6	30.2	30.1	30.2	30.3	29.8	41.8	42.1	42.6	42.6	43.0	43.0	42.4
			lb-in	264	262	267	266	267	268	264	370	373	377	377	381	381	374
Peak Current	Nom	I_p	A_{rms}	14.6	16.2	28.8	36.0	40.2	56	65	13.4	16.8	29.7	33.3	41.4	52.2	67.2
75 Vdc																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-			-	-	-	-	-
120 Vac (160 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-	-	-	-	-	-	-	-
240 Vac (320 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	11.2	10.4	10.0	9.50	8.1	6.5	-	-	14.9	14.4	14.3	13	11.9
			lb-in	-	99	92	89	84.1	72	58	-	-	132	127	127	115	105
Rated Speed		N_{rtd}	rpm	-	1000	2000	2500	3000	4500	5500	-	-	1500	1800	2000	3000	3500
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	1.17	2.18	2.62	2.98	3.82	3.74	-	-	2.34	2.71	2.99	4.08	4.36
			Hp	-	1.57	2.92	3.51	4.00	5.12	5.02	-	-	3.14	3.63	4.01	5.47	5.85
400 Vac (560 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	10.4	10.2	9	7.42	5.70	-	-	14.9	14.6	12.9	12.9	11.3	9.6⑯	-
			lb-in	92	90.3	80	65.7	50.4	-	-	132	129	114	114	100	85⑯	-
Rated Speed		N_{rtd}	rpm	1800	2000	3500	5000	6000	-	-	1200	1500	3000	3000	4000	5000⑯	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	1.96	2.14	3.3	3.89	3.58	-	-	1.87	2.29	4.05	4.05	4.73	5.03⑯	-
			Hp	2.63	2.86	4.42	5.21	4.80	-	-	2.51	3.08	5.43	5.43	6.34	6.74⑯	-
480 Vac (640 Vdc)																	
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	10.2	9.9	8	5.74	5.70	-	-	14.6	14.2	12	12.0	10.5	-	-
			lb-in	90	87.6	71	50.8	50.4	-	-	129	126	106	106	92.9	-	-
Rated Speed		N_{rtd}	rpm	2000	2400	4500	6000	6000	-	-	1500	1800	3500	3500	4500	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	2.14	2.49	3.77	3.61	3.58	-	-	2.29	2.68	4.4	4.4	4.95	-	-
			Hp	2.86	3.34	5.05	4.84	4.80	-	-	3.07	3.59	5.9	5.90	6.63	-	-

AKM62-63 Motor Parameters

				AKM62							AKM63						
Parameters	Tol	Sym	Units	G	H	K	L	M	P	Q	G	H	K	L	M	N	Q
Torque Constant ①	±10%	K_t	Nm/A_{rms}	2.47	2.21	1.27	1.03	0.92	0.66	0.55	3.7	2.98	1.71	1.52	1.24	0.98	0.75
			$lb\text{-}in/A_{rms}$	21.9	19.6	11.2	9.1	8.1	5.8	4.87	32.7	26.4	15.1	13.5	11.0	8.7	6.6
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	159	142	82.1	65.5	58.8	42.2	35.5	238	192	110	98.2	79.9	63.3	48.3
Motor Constant	Nom	K_m	N-m/√W	0.992	0.989	1.006	0.949	0.984	0.984	1.00	1.288	1.32	1.308	1.26	1.30	1.281	1.28
			lb-in/√W	8.80	8.75	8.88	8.40	8.71	8.65	8.85	11.38	11.7	11.55	11.2	11.5	11.37	11.3
Resistance (line-line) ⑥	±10%	R_m	ohm	4.13	3.3	1.08	0.71	0.57	0.3	0.24	5.5	3.43	1.14	0.94	0.61	0.39	0.23
Inductance (line-line)		L	mH	31.7	25.4	8.5	5.4	4.4	2.2	1.6	43.5	28.1	9.3	7.4	4.9	3.1	1.8
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	17							24						
			$lb\text{-}in\text{-}s^2$	0.015							0.021						
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.668							0.668						
			$lb\text{-}in\text{-}s^2$	5.91E-04							5.91E-04						
Weight (w/o brake) ⑪		W	kg	8.9							11.1						
			lb	19.6							24.4						
Static Friction ①⑩		T_f	Nm	0.05							0.1						
			lb-in	0.44							0.9						
Viscous Damping ①		K_{dv}	Nm/krpm	0.04							0.06						
			lb-in/krpm	0.35							0.53						
Thermal Time Constant		TCT	minutes	20							25						
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	0.46							0.41						
Operating Ambient Temperature Range ⑬⑭⑮			°C	-20 to 40							-20 to 40						
Pole Pairs				5							5						
Heat Sink Size				18"x18"x1/2" Aluminum Plate							18"x18"x1/2" Aluminum Plate						

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake option reduces continuous torque ratings by:
AKM62 = 0.5 Nm AKM63 = 0.9 Nm AKM64 = 1.3 Nm AKM65 = 1.7 Nm
⑧ Non-Resolver feedback options reduce continuous torque ratings by:
AKM62 = 0.9 Nm AKM63 = 1.2 Nm AKM64 = 1.5 Nm AKM65 = 1.8 Nm
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM62 = 1.6 Nm AKM63 = 2.4 Nm AKM64 = 3.1 Nm AKM65 = 4.0 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.25 Nm (2.21 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 2.2 kg (4.84 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.
⑯ High speed continuous performance could be reduced by additional losses due to combination of source voltage, winding inductance, and servo drive PWM frequency. Please contact Kollmorgen Customer Support with your specific applications requirements.

Related Resources:

AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)

AKM6x Series Motor Specifications

AKM64-65 Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM64				AKM65				
Parameters	Tol	Sym	Units	K	L	P	Q	K	L	M	N	P
Max Rated Voltage ⑫	Max	–	Vac	480	480	480	480	480	480	480	480	480
			Vdc	640	640	640	640	640	640	640	640	640
Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	20.8	21.0	20.4	20.6	24.8	25.0	25.0	24.3	24.5
			lb-in	184	186	181	182	219	221	221	215	217
Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	9.2	12.8	18.6	20.7	9.8	12.2	13.6	17.8	19.8
Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	16.6	16.8	16.3	16.5	19.8	20	20.0	19.4	19.6
			lb-in	147	149	144	146	175	177	177	172	173
Max Mechanical Speed ⑤	Nom	N_{max}	rpm	6000	6000	6000	6000	6000	6000	6000	6000	6000
Peak Torque ①②	Nom	T_p	Nm	53	54	53	53	65	65	65	64	64
			lb-in	469	478	469	469	575	575	575	566	566
Peak Current	Nom	I_p	A_{rms}	27.5	38.4	56	62	29.4	36.6	40.9	53	59
75 Vdc												
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-
Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-	-	-
120 Vac (160 Vdc)												
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-
Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-	-	-
240 Vac (320 Vdc)												
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	18.8	18.4	16	15.3	22.8	22.4	21.9	19.8	19.1
			lb-in	166	163	142	135	202	198	194	175	169
Rated Speed		N_{rtd}	rpm	1200	1500	2500	3000	1000	1300	1500	2000	2400
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	2.36	2.89	4.19	4.81	2.39	3.05	3.44	4.15	4.8
			Hp	3.17	3.87	5.62	6.45	3.2	4.09	4.61	5.56	6.44
400 Vac (560 Vdc)												
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	17.2	15.6	11.9⑯	-	20.2	19.2	18.8	16	14.9⑯
			lb-in	152	138	105⑯	-	179	170	166	142	132⑯
Rated Speed		N_{rtd}	rpm	2000	3000	4500⑯	-	2000	2500	2700	3500	4000⑯
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	3.60	4.90	5.61⑯	-	4.23	5.03	5.32	5.86	6.24⑯
			Hp	4.83	6.57	7.52⑯	-	5.67	6.74	7.13	7.86	8.37⑯
480 Vac (640 Vdc)												
Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	16.3	14.4	-	-	19.7	18.3	18.1	14.7⑯	-
			lb-in	144	127	-	-	174	162	160	130⑯	-
Rated Speed		N_{rtd}	rpm	2500	3500	-	-	2200	2800	3000	4000⑯	-
Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	4.27	5.28	-	-	4.54	5.37	5.69	6.16⑯	-
			Hp	5.72	7.07	-	-	6.08	7.2	7.62	8.25⑯	-

AKM64–65 Motor Parameters

				AKM64				AKM65				
Parameters	Tol	Sym	Units	K	L	P	Q	K	L	M	N	P
Torque Constant ①	±10%	K_t	Nm/A_{rms}	2.28	1.66	1.1	0.99	2.55	2.07	1.85	1.38	1.26
			$lb\text{-}in/A_{rms}$	20.2	14.7	9.7	8.8	22.6	18.3	16.4	12.2	11.2
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	147	107	71	0.64	164	133	119	88.8	80.5
Motor Constant	Nom	K_m	$N\text{-}m/\sqrt{W}$	1.57	1.57	1.497	1.44	1.785	1.81	1.77	1.718	1.75
			$lb\text{-}in/\sqrt{W}$	13.9	13.9	13.20	12.8	15.81	16.0	15.6	15.19	15.4
Resistance (line-line) ⑥	±10%	R_m	ohm	1.41	0.75	0.36	0.30	1.35	0.90	0.73	0.43	0.36
Inductance (line-line)		L	mH	11.8	6.2	2.8	1.9	11.4	7.6	6.1	3.4	2.8
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	32				40				
			$lb\text{-}in\text{-}s^2$	0.028				0.035				
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	0.668				0.668				
			$lb\text{-}in\text{-}s^2$	5.91E-04				5.91E-04				
Weight (w/o brake) ⑪		W	kg	13.3				15.4				
			lb	29.3				33.9				
Static Friction ①⑩		T_f	Nm	0.15				0.2				
			lb-in	1.3				1.8				
Viscous Damping ①		K_{dv}	Nm/krpm	0.08				0.1				
			lb-in/krpm	0.71				0.9				
Thermal Time Constant		TCT	minutes	30				35				
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	0.38				0.35				
Operating Ambient Temperature Range ⑬⑭⑮			°C	-20 to 40				-20 to 40				
Pole Pairs				5				5				
Heat Sink Size				18″x18″x1/2″ Aluminum Plate				18″x18″x1/2″ Aluminum Plate				

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake option reduces continuous torque ratings by:
AKM62 = 0.5 Nm AKM63 = 0.9 Nm AKM64 = 1.3 Nm AKM65 = 1.7 Nm
⑧ Non-Resolver feedback options reduce continuous torque ratings by:
AKM62 = 0.9 Nm AKM63 = 1.2 Nm AKM64 = 1.5 Nm AKM65 = 1.8 Nm
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM62 = 1.6 Nm AKM63 = 2.4 Nm AKM64 = 3.1 Nm AKM65 = 4.0 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.25 Nm (2.21 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 2.2 kg (4.84 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.
⑯ High speed continuous performance could be reduced by additional losses due to combination of source voltage, winding inductance, and servo drive PWM frequency. Please contact Kollmorgen Customer Support with your specific applications requirements.

Related Resources:


AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)


AKM6x Series Motor Specifications


AKM6x Frame Dimensional Drawings

AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools


C- connector option









G- connector option



9- connector option



Shaft-keyway dimensions



Dimensional data tables for callouts are located on the following page.

AKM6x Frame Dimensional Data

AKM6x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"	Shaft Dia. w/ Key "L"
AC	11.00 [0.433]	130 [5.1181]	165.00 [6.496]	–	D M12 DIN 332	32 [1.2598]	58 [2.28]	–
AN	11.00 [0.433]	130 [5.1181]	165.00 [6.496]	–	D M12 DIN 332	32 [1.2598]	58 [2.28]	–
GC	11.00 [0.433]	130 [5.1181]	165.00 [6.496]	–	D M8 DIN 332	24 [0.9449]	50 [1.97]	–
GN	11.00 [0.433]	130 [5.1181]	165.00 [6.496]	–	D M8 DIN 332	24 [0.9449]	50 [1.97]	–
KK	9.00 [0.354]	110 [4.3307]	145.00 [5.709]	165 [6.496]	–	28 [1.1024]	60 [2.36]	31 [1.220]
LK	3/18 - 16 UNC-2B	114.3 [4.5000]	149.225 [5.875]	165 [6.496]	–	28.580 [1.1250]	69.85 [2.75]	31.39 [1.236]

Mounting Flange-Shaft	Key Width "M"	Key Length "N"	Shaft Dia. w/ Key "P"	Key Width "R"	"S"	Key Length "T"	"U"	"V"	"W"
AC	–	–	35 [1.378]	10 [0.3937]	5.00 [0.197]	45 [1.772]	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
AN	–	–	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
GC	–	–	27 [1.063]	8 [0.3150]	5.00 [0.197]	40 [1.575]	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
GN	–	–	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
KK	8 [0.3150]	50 [1.969]	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
LK	6.35 [2.75]	38.1 [1.500]	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]

AKM6x Motor Length Dimensional Data

	No Brake (N)		
	X	Y MAX	Z MAX
Connector	C-, 9-, G	C-, 9-, G	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex	Ax, Dx, Lx, Gx
AKM62	130.5 [5.14]	153.7 [6.05]	172.2 [6.78]
AKM63	155.5 [6.12]	178.7 [7.04]	197.2 [7.76]
AKM64	180.5 [7.11]	203.7 [8.02]	222.2 [8.75]
AKM65	205.5 [8.09]	228.7 [9]	247.2 [9.73]

	Brake (2)		
	X	Z MAX	
Connector	C-, 9-, G	C-, 9-, G	C-, 9-, G-
Feedback Option	R-, C-, 1-, 2-, Cx, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Cx, Ex	Ax, Dx, Lx, Gx
AKM62	130.5 [5.14]	200.7 [7.9]	219.7 [8.65]
AKM63	155.5 [6.12]	225.7 [8.89]	244.7 [9.63]
AKM64	180.5 [7.11]	250.7 [9.87]	269.7 [10.62]
AKM65	205.5 [8.09]	275.7 [10.85]	294.7 [11.6]

Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:
Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

AKM7x Series Motor Specifications

AKM7x Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM72					AKM73				AKM74		
Parameters	Tol	Symbol	Units	K	L	M	P	Q	L	M	P	Q	L	P	Q
Max Rated Voltage ⑫	Max	–	Vac	480	480	480	480	480	480	480	480	480	480	480	480
			Vdc	640	640	640	640	640	640	640	640	640	640	640	640
Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	29.7	30	30	29.4	29.5	42	42	41.6	41.5	53.0	52.5	52.2
			lb-in	263	266	266	260	261	372	372	368	367	469	465	426
Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	9.3	11.5	13.0	18.7	23.5	12.1	13.6	19.5	24.5	12.8	18.4	26.1
Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	23.8	24	24	23.5	23.6	33.6	33.6	33.3	33.2	42.4	42.0	41.8
			lb-in	211	212	212	208	209	297	297	295	294	375	372	370
Max Mechanical Speed ⑤	Nom	N_{max}	rpm	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
Peak Torque ①②	Nom	T_p	Nm	79	80	80	78	78	113	113	111	111	143	142	141
			lb-in	699	708	708	690	690	1000	1000	985	982	1269	1253	1250
Peak Current	Nom	I_p	A_{rms}	27.9	34.5	39.0	56.1	70.5	36.3	40.8	58.6	73.5	38.5	55.2	78.3
75 Vdc: Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-	-	-	-
75 Vdc: Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-	-	-	-
75 Vdc: Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-	-	-	-	-	-
120 Vac (160 Vdc): Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	-	-	-	-	-	-	-	-	-
			lb-in	-	-	-	-	-	-	-	-	-	-	-	-
120 Vac (160 Vdc): Rated Speed		N_{rtd}	rpm	-	-	-	-	-	-	-	-	-	-	-	-
120 Vac (160 Vdc): Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	-	-	-	-	-	-	-	-	-
			Hp	-	-	-	-	-	-	-	-	-	-	-	-
240 Vac (320 Vdc): Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-	23.8	23.3	-	-	34.7	33.4	-	-	41.9
			lb-in	-	-	-	211	205	-	-	307	296	-	-	371
240 Vac (320 Vdc): Rated Speed		N_{rtd}	rpm	-	-	-	1800	2000	-	-	1300	1500	-	-	1300
240 Vac (320 Vdc): Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-	4.49	4.86	-	-	4.72	5.25	-	-	5.7
			Hp	-	-	-	6.01	6.52	-	-	6.33	7.04	-	-	7.64
400 Vac (560 Vdc): Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	25.1	24.3	23.6	20.1	16.3	34.4	33.8	28.5	25.2	43.5	39.6	31.5
			lb-in	222	215	209	178	144	304	299	252	223	385	350	279
400 Vac (560 Vdc): Rated Speed		N_{rtd}	rpm	1500	1800	2000	3000	4000	1400	1500	2400	3000	1200	1800	2500
400 Vac (560 Vdc): Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	3.94	4.58	4.94	6.31	6.83	5.04	5.31	7.16	7.92	5.47	7.46	8.25
			Hp	5.28	6.14	6.62	8.46	9.16	6.76	7.12	9.60	10.6	7.33	10.0	11.1
480 Vac (640 Vdc): Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	24.0	23.6	22.1	18.2	14.1⑯	33.8	32.1	26.3	22.0	41.5	35.9	27.3
			lb-in	212	209	196	161	125⑯	299	284	233	195	367	318	242
480 Vac (640 Vdc): Rated Speed		N_{rtd}	rpm	1800	2000	2500	3500	4500⑯	1500	1800	2800	3500	1400	2000	3000
480 Vac (640 Vdc): Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	4.52	4.94	5.79	6.67	6.65⑯	5.31	6.05	7.71	8.07	6.08	7.52	8.58
			Hp	6.06	6.62	7.76	8.94	8.91⑯	7.12	8.11	10.3	10.8	8.16	10.1	11.5

See following page for notes.

AKM7x Motor Parameters

				AKM72					AKM73				AKM74		
Parameters	Tol	Symbol	Units	K	L	M	P	Q	L	M	P	Q	L	P	Q
Torque Constant ①	±10%	K_t	Nm/A_{rms}	3.23	2.62	2.33	1.58	1.26	3.49	3.11	2.13	1.69	4.14	2.84	2.0
			$lb\text{-}in/A_{rms}$	28.6	23.2	20.6	14.0	11.2	31.0	27.4	18.9	15	36.6	25.1	17.7
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	208	169	150	102	81	225	200	137	109	266	183	129
Motor Constant	Nom	K_m	N-m/√W	2.261	2.21	2.290	2.18	2.08	2.93	2.903	2.82	2.67	3.51	3.38	3.27
			lb-in/√W	20.02	19.6	20.25	19.3	18.4	25.9	25.66	25.0	23.6	31.0	29.9	28.9
Resistance (line-line) ⑥	±10%	R_m	ohm	1.36	0.92	0.69	0.35	0.23	0.95	0.76	0.38	0.25	0.93	0.47	0.24
Inductance (line-line)		L	mH	20.7	13.6	10.8	5.0	3.2	15.7	12.4	5.9	3.7	16.4	7.7	3.8
Inertia (includes Resolver feedback) ③	±10%	J_m	$kg\text{-}cm^2$	65					92				120		
			$lb\text{-}in\text{-}s^2$	0.057					0.082				0.11		
Optional Brake Inertia (additional)	±10%	J_m	$kg\text{-}cm^2$	1.589					1.589				1.589		
			$lb\text{-}in\text{-}s^2$	1.41E-03					1.41E-03				1.41E-03		
Weight (w/o brake) ⑪		W	kg	19.7					26.7				33.6		
			lb	43.4					58.8				74.0		
Static Friction ①⑩		T_f	Nm	0.16					0.24				0.33		
			lb-in	1.4					2.1				2.9		
Viscous Damping ①		K_{dv}	Nm/krpm	0.06					0.13				0.2		
			lb-in/krpm	0.5					1.2				1.8		
Thermal Time Constant		TCT	minutes	46					53				60		
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	0.39					0.33				0.30		
Operating Ambient Temperature Range ⑬⑭⑮			°C	-20 to 40					-20 to 40				-20 to 40		
Pole Pairs				5					5				5		
Heat Sink Size				18″x18″x1/2″ Aluminum Plate					18″x18″x1/2″ Aluminum Plate				18″x18″x1/2″ Aluminum Plate		

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:
① Motor winding temperature rise, ΔT=100°C, at 40°C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25°C.
⑦ Brake option reduces continuous torque ratings by 1 Nm.
⑧ Non-Resolver feedback options reduce continuous torque ratings by:
AKM72 = 2.0 Nm AKM73 = 2.7 Nm AKM74 = 3.4 Nm
⑨ Motors with non-resolver feedback and brake option, reduce continuous torque by:
AKM72 = 3.9 Nm AKM73 = 5.1 Nm AKM74 = 6.2 Nm
⑩ For motors with optional shaft seal, reduce torque shown by 0.25 Nm (2.21 lb-in), and increase T_f by the same amount.
⑪ Brake option increases weight by 3.1 kg (6.82 lb).
⑫ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑬ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑭ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑮ Operation outside of this range may be possible. Please contact Kollmorgen Customer Support with your application requirements.
⑯ High speed continuous performance could be reduced by additional losses due to combination of source voltage, winding inductance, and servo drive PWM frequency. Please contact Kollmorgen Customer Support with your specific applications requirements.

Related Resources:


AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)


AKM7x Series Motor Specifications


AKM7x Frame Dimensional Drawings

AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools


C- connector option









G- connector option



H- connector option



Shaft-keyway dimensions



Dimensional data tables for callouts are located on the following page.

AKM7x Frame Dimensional Data

AKM7x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"	Shaft Dia. w/ Key "L"
AC	13.50 [0.531]	180 [7.0866]	215.00 [8.465]	–	D M12 DIN 332	38 [1.496]	80 [3.15]	–
AN	13.50 [0.531]	180 [7.0866]	215.00 [8.465]	–	D M12 DIN 332	38 [1.496]	80 [3.15]	–
GC	13.50 [0.531]	180 [7.0866]	215.00 [8.465]	–	D M12 DIN 332	32 [1.5298]	58.5 [2.30]	–
GN	13.50 [0.531]	180 [7.0866]	215.00 [8.465]	–	D M12 DIN 332	32 [1.5298]	58.5 [2.30]	–
KK	13.50 [0.531]	114.3 [4.5000]	200 [7.874]	225 [8.858]	–	35 [1.3779]	79 [3.11]	38 [1.496]

Mounting Flange-Shaft	Key Width "M"	Key Length "N"	Shaft Dia. w/ Key "P"	Key Width "R"	"S"	Key Length "T"	"U"	"V"	"W"
AC	–	–	41 [1.614]	10 [0.3937]	5.00 [0.197]	70 [2.756]	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
AN	–	–	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
GC	–	–	35 [1.378]	108 [0.3937]	4 [0.157]	50 [1.969]	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
GN	–	–	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
KK	10 [0.3937]	70 [2.756]	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]

AKM7x Motor Length Dimensional Data

	No Brake (N)		
	X	Y MAX	Z MAX
Connector	C-, G-, H-	C-, G-, H-	C-, G-, H-
Feedback Option	R-, C-, 1-, 2-, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Ex	Ax, Dx, Lx, Gx
AKM72	164.5 [6.48]	192.5 [7.58]	201.7 [7.94]
AKM73	198.5 [7.81]	226.5 [8.92]	235.7 [9.28]
AKM74	232.5 [9.15]	260.5 [10.26]	269.7 [10.62]

	Brake (2)		
	X	Z MAX	
Connector	C-, G-, H-	C-, G-, H-	C-, G-, H-
Feedback Option	R-, C-, 1-, 2-, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Ex	Ax, Dx, Lx, Gx
AKM72	164.5 [6.48]	234.5 [9.23]	253.3 [9.97]
AKM73	198.5 [7.81]	268.5 [10.57]	287.3 [11.31]
AKM74	232.5 [9.15]	302.5 [11.91]	321.3 [12.65]

Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:
Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

AKM8x Series Motor Specifications

AKM8x Performance Data – Up to 480 Vac (640 Vdc Bus) voltage

					AKM82	AKM83	AKM84
	Parameters	Tol	Symbol	Units	AKM82T	AKM83T	AKM84T
	Max Rated Voltage ⑪	Max	–	Vac	480	480	480
				Vdc	640	640	640
	Continuous Torque (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	T_{cs}	Nm	75	130	180
				lb-in	664	1151	1593
	Continuous Current (Stall) for ΔT winding = 100°C ①②⑦⑧⑨	Nom	I_{cs}	A_{rms}	48	65	67
	Continuous Torque (Stall) for ΔT winding = 60°C ②	Nom	T_{cs}	Nm	58.1	104	144
				lb-in	514	920	1274
	Max Mechanical Speed ⑤	Nom	N_{max}	rpm	3000	3000	3000
	Peak Torque ①②	Nom	T_p	Nm	175	299	434
				lb-in	1549	2646	3841
	Peak Current	Nom	I_p	A_{rms}	144	263.9	201
75 Vdc	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-
				lb-in	-	-	-
	Rated Speed		N_{rtd}	rpm	-	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-
				Hp	-	-	-
120 Vac (160 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-
				lb-in	-	-	-
	Rated Speed		N_{rtd}	rpm	-	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-
				Hp	-	-	-
240 Vac (320 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	-	-	-
				lb-in	-	-	-
	Rated Speed		N_{rtd}	rpm	-	-	-
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	-	-	-
				Hp	-	-	-
400 Vac (560 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	47.5	70	105
				lb-in	420	620	929
	Rated Speed		N_{rtd}	rpm	2500	2200	1800
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	12.4	16.1	19.8
				Hp	16.65	21.62	26.58
480 Vac (640 Vdc)	Rated Torque (speed) ①②⑦⑧⑨⑩		T_{rtd}	Nm	38	60	93
				lb-in	336	531	823
	Rated Speed		N_{rtd}	rpm	3000	2500	2000
	Rated Power (speed) ①②⑦⑧⑨		P_{rtd}	kW	11.9	15.7	19.5
				Hp	16.0	21.0	26.1

See following page for notes.

AKM8x Performance Data – Up to 480 Vac (640 Vdc Bus) voltage (Continued)

				AKM82	AKM83	AKM84
Parameters	Tol	Symbol	Units	AKM82T	AKM83T	AKM84T
Torque Constant ①	±10%	K_t	Nm/A_{rms}	1.68	2.17	2.75
			$lb\text{-}in/A_{rms}$	14.9	19.2	24.3
Back EMF Constant ⑥	±10%	K_e	$V_{rms}/krpm$	108	140	177
Motor Constant	Nom	K_m	$N\text{-}m/\sqrt{W}$	4.31	6.94	9.15
			$lb\text{-}in/\sqrt{W}$	38.1	61.4	81.0
Resistance (line-line) ⑥	±10%	R_m	ohm	0.092	0.061	0.058
Inductance (line-line)		L	mH	2.73	2.36	2.5
Inertia (includes Resolver feedback) ③		J_m	$kg\text{-}cm^2$	172	334	495
			$lb\text{-}in\text{-}s^2$	0.15	0.29	0.43
Optional Brake Inertia (additional)		J_m	$kg\text{-}cm^2$	4.438	4.438	4.438
			$lb\text{-}in\text{-}s^2$	3.930E-03	3.930E-03	3.93E-03
Weight (w/o brake) ⑧		W	kg	65	85	105
			lb	143.3	187.4	231.5
Static Friction ①⑩		T_f	Nm	1.7	1.8	2.30
			lb-in	15.05	15.93	20.36
Viscous Damping ①		K_{dv}	Nm/krpm	0.35	0.95	1.6
			lb-in/krpm	3.10	8.41	14.16
Thermal Time Constant		TCT	minutes	71	94	116
Thermal Resistance		$R_{thw\text{-}a}$	°C/W	0.225	0.203	0.183
Operating Ambient Temperature Range ⑫ ⑬ ⑭			°C	-20 to 40	-20 to 40	-20 to 40
Pole Pairs				5	5	5
Heat Sink Size				18″x18″x1/2″ Aluminum Plate	18″x18″x1/2″ Aluminum Plate	18″x18″x1/2″ Aluminum Plate

Additional windings may exist. Please contact Kollmorgen Customer Support for further information or to request custom winding options for your application requirements.

Notes:

① Motor winding temperature rise, ΔT = 100° C, at 40° C ambient.
② All data referenced to sinusoidal commutation.
③ Add parking brake if applicable for total inertia.
④ Motor with standard heat sink.
⑤ May be limited at some values of Vbus.
⑥ Measured at 25° C.
⑦ Brake option decreases continuous torque by 6 Nm
⑧ Brake option increases weight by 8.1 kg (17.8 lb).
⑨ Non-Resolver feedback options reduce continuous torque ratings by: AKM82 = 9 Nm, AKM83 = 6 Nm, AKM84 = 18 Nm
⑩ Motor with non-resolver feedback and brake options reduce continuous torque ratings by: AKM82 = 17 Nm, AKM83 = 16 Nm, AKM84 = 28 Nm
⑪ Motors can be operated up to 480 Vac. For performances curves at voltages, listed or unlisted, please use our online Performance Curve Generator Tool.
⑫ Brake option will operate in this range in a non-condensing environment. See the Brake Option section for more information.
⑬ "AA" or "AB" BiSS feedback lower limit is -15°C; all other feedbacks meet or exceed this range.
⑭ Operation ABOVE 40°C may be possible. Please contact Kollmorgen Customer Support with your application requirements.

Related Resources:


AKM® Servo Motor Quick Guide (for typical torque/speed performance)
Performance Curve Generator Tool (generate AKM model specific performance curves)
Brake Option (detailed brake specifications)

AKM8x Series Motor Specifications

AKM8x Frame with Terminal Box Dimensional Drawings

AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools

T- connector option




Shaft-keyway dimensions


Dimensional data tables for callouts are located on the page following the outline drawings.

AKM82 Frame with Rotatable IP65 Connectors Dimensional Drawings


AKM 2D/3D CAD models can be found at Kollmorgen.com/DesignTools

H- connector option





Shaft-keyway dimensions



Dimensional data tables for callouts are located on the page following the outline drawings.

AKM8x Series Motor Specifications

AKM82 Frame Dimensional Data

AKM8x Mounting Flange-Shaft Dimensional Data

Mounting Flange-Shaft	Hole Diameter "C"	Pilot Diameter "D"	Bolt Circle Dia. "E"	"F"	"H"	Shaft Diameter "J"	Shaft Length "K"
AC	18.5 [0.728]	250 [9.8425]	300 [11.811]	–	D M16 DIN 332	48 [1.8898]	110 [4.33]
AN	18.5 [0.728]	250 [9.8425]	300 [11.811]	–	D M16 DIN 332	48 [1.8898]	110 [4.33]
CC	14.5 [0.571]	230 [9.055]	265 [10.433]	300 [11.811]	D M16 DIN 332	48 [1.8898]	110 [4.33]
CN	14.5 [0.571]	230 [9.055]	265 [10.433]	300 [11.811]	D M16 DIN 332	48 [1.8898]	82 [3.228]
HC	14.5 [0.571]	230 [9.055]	265 [10.433]	300 [11.811]	D M16 DIN 332	42 [1.6535]	82 [3.228]
HN	14.5 [0.571]	230 [9.055]	265 [10.433]	300 [11.811]	D M16 DIN 332	42 [1.6535]	82 [3.228]
GC	18.5 [0.728]	250 [9.8425]	300 [11.811]	–	D M16 DIN 332	48 [1.8898]	82 [3.228]
GN	18.5 [0.728]	250 [9.8425]	300 [11.811]	–	D M16 DIN 332	48 [1.8898]	82 [3.228]
MC	18.5 [0.728]	250 [9.8425]	300 [11.811]	–	D M16 DIN 332	48 [1.8898]	110 [4.33]
MN	18.5 [0.728]	250 [9.8425]	300 [11.811]	–	D M16 DIN 332	48 [1.8898]	110 [4.33]
TC	14.5 [0.571]	230 [9.055]	265 [10.433]	300 [11.811]	D M16 DIN 332	48 [1.8898]	110 [4.33]
TN	14.5 [0.571]	230 [9.055]	265 [10.433]	300 [11.811]	D M16 DIN 332	48 [1.8898]	110 [4.33]

REINFORCED BEARNGS

Mounting Flange-Shaft	Shaft Dia. w/ Key "P"	Key Width "R"	"S"	Key Length "T"	"U"	"V"	"W"
AC	51.5 [2.028]	14 [0.5512]	10 [0.394]	90 [3.543]	0.050 [0.0019]	0.125 [0.0049]	0.125 [0.0049]
AN	–	–	–	–	0.050 [0.0019]	0.125 [0.0049]	0.125 [0.0049]
CC	51.5 [2.028]	14 [0.5512]	10 [0.394]	90 [3.543]	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
CN	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
HC	45 [1.7772]	12 [0.5512]	8 [0.315]	63 [2.480]	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
HN	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
GC	51.5 [2.028]	14 [0.5512]	8 [0.315]	63 [2.480]	0.050 [0.0019]	0.125 [0.0049]	0.125 [0.0049]
GN	–	–	–	–	0.050 [0.0019]	0.125 [0.0049]	0.125 [0.0049]
MC	51.5 [2.028]	14 [0.5512]	10 [0.394]	90 [3.543]	0.050 [0.0019]	0.125 [0.0049]	0.125 [0.0049]
MN	–	–	–	–	0.050 [0.0019]	0.125 [0.0049]	0.125 [0.0049]
TC	51.5 [2.028]	14 [0.5512]	10 [0.394]	90 [3.543]	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]
TN	–	–	–	–	0.050 [0.0019]	0.100 [0.0039]	0.100 [0.0039]

REINFORCED BEARNGS

AKM8x Motor Length Dimensional Data

		No Brake (N)	Brake (2)
	X	Y MAX	Z MAX
Connector	H-, T-	H-, T-	H-, T-
Feedback Option	R-, C-, 1-, 2-, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Ex, Ax, Dx, Lx, Gx	R-, C-, 1-, 2-, Ex, Ax, Dx, Lx, Gx
AKM82 "H" Connector	223 [8.78]	267 [10.51]	333 [13.11]
AKM82 "T" TERMINAL BOX	255 [10.04]	267 [10.51]	333 [13.11]
AKM83 "T" TERMINAL BOX	335.5 [13.21]	347.5 [13.68]	413.5 [16.28]
AKM84 "T" TERMINAL BOX	416 [16.38]	428 [16.85]	494 [19.45]

Note 1: Dimensions are in mm [inches].
Note 2: Product designed in metric. English conversions provided for reference only.

Related Resources:

Feedback Options and Specifications
Connector Options and Pinouts
Brake Option

Brake Option

Failsafe, Holding Brake

The holding brake is designed to provide static holding torque to the motor shaft with the brake coil de-energized. The brake must first be released (coil energized) prior to commanding motor rotation as determined by its drop-out time. The brake is intended for holding or "parking" of a stationary motor. It is not intended for dynamic braking. There should be absolutely no motion of the rotor when power is removed from the brake coil.

AKM Motor Brake Specifications

Motor Family	Minimum Static Torque @120°C		Weight		Power Consumption @24V, 20°C	Current @24V, 20°C	Inertia		Closing Time (engage)	Opening Time (release)	Backlash	
											Maximum	Typical
	Nm	lb-in	Kg	lb	Watts ±7%	ADC	kg-cm²	lb-in-sec²	msec	msec	deg.	deg.
AKM1	0.41	3.63	0.19	0.42	6.3	0.27	0.0013	1.20E-06	22	45	1.15	0.53
AKM2	1.42	12.6	0.27	0.59	8.4	0.35	0.013	1.20E-05	36	45	1.01	0.46
AKM3	2.5	22.1	0.36	0.79	10.2	0.42	0.014	1.20E-05	20	50	1.01	0.46
AKM4	5.3	46.9	0.69	1.52	12.7	0.53	0.058	5.12E-05	30	75	0.81	0.37
AKM5	14.5	128	1.2	2.64	19.7	0.81	0.166	1.47E-04	30	115	0.71	0.31
AKM6	25	221	2.2	4.81	25.7	1.07	0.668	5.91E-04	40	155	0.51	0.24
AKM7	53	469	3.1	6.82	35.6	1.48	1.589	1.41E-03	70	170	0.44	0.20
AKM8	150	1330	8.1	17.8	52.3	2.04	4.438	3.93E-03	100	300	0.44	0.20

Notes:
1. Contamination of the motor internal compartment by oil or other foreign materials will result in failure of the brake. Check the suitability of motor sealing for the working environment.
2. Operating Voltage: 24 Vdc ± 10%.
3. Maximum backlash is calculated using worst-case tolerancing, and typical backlash is calculated using statistical tolerancing.
4. Brake Operating Temperature Range: -20C to 120C. Sub-zero temperatures present a freezing risk for condensation which could prevent correct brake operation.

AKM Feedback Options

AKM Servo Motor Feedback Summary with AKD Family Servo Drives

Feedback Unit Options

				Feedback Resolution				
Code	Designation	AKM Frame Size	Single-Turn or Multi-Turn	Device Resolution (Sin/Cos per Rev., Bits or Lines/Rev.)	AKD Internal Resolution	AKD2G Internal Resolution	# of Absolute Revs.	Accuracy (± arc-mins)
1-	Commutating Encoder	1-8	Single-Turn	1024 Lines	4,096	4,096	None	1
2-				2048 Lines	8,192	8,192		
ED		2-8		500 Lines	2,000	2,000		
EE				1000 Lines	4,000	4,000		
EF				2000 Lines	8,000	8,000		
EG				2500 Lines	10,000	10,000		
EH				5000 Lines	20,000	20,000		
EJ				10000 Lines	40,000	40,000		
EM				4096 Lines	16,384	16,384		
EN				8192 Lines	32,768	32,768		
AA	BiSS B Optical Sine Encoder	2-4	Single-turn	2048 Sin/Cos	27-Bits	32-Bits	1	0.6
		5-8						
AB		2-4	Multi-turn				4,096	
		5-8						
C-	SFD Smart Feedback Device	1	Single-turn	24-Bits	24-Bits	24-Bits	1	15
		2-4						8
		5-8						9
CA	SFD3 Smart Feedback Device, Gen. 3	1	Single-turn	24-Bits				15
		2-4						8
		5-6						9
CB	SFD-M Smart Feedback Device, Multi-turn	2-6	Multi-turn	24-Bits	24-Bits	24-Bits	65,536	1
GE	HIPERFACE DSL® Optical Encoder	2-6	Single-turn	18-Bits	18-Bits	18-Bits	1	1.33
GF			Multi-turn				4,096	
GA/GJ*	HIPERFACE Optical Sin/Cos Encoder	2-8	Single-turn	128 Sin/Cos	23-Bits	31-Bits	1	1.33
GB/GK*			Multi-turn				4,096	
GP**	HIPERFACE Capacitive Encoder	1	Single-turn	16 Sin/Cos	20-Bits	28-Bits	1	4.8
GR**			Multi-turn				4,096	
DA	EnDat® 2.2/01 Optical Sine Encoder	2-4	Single-turn	512 Sin/Cos	25-Bits	32-Bits	1	1
		5-8		2048 Sin/Cos	27-Bits			0.333
DB		2-4	Multi-turn	512 Sin/Cos	25-Bits		4,096	1
		5-8		2048 Sin/Cos	27-Bits			0.333
LA	EnDat® 2.2/22 Inductive Encoder	2-3	Single-turn	18-Bits	18-Bits	18-Bits	1	4.67
		4-8		19-Bits	19-Bits	19-Bits		3
LB		2-3	Multi-turn	18-Bits	18-Bits	18-Bits	4,096	4.67
		4-8		19-Bits	19-Bits	19-Bits		3
R-	Resolver Inductive Encoder	1	Single-Turn	1 pole pair (16-Bits)	16-Bits	16-Bits	1	15
		2-4						10
		5-8						9

*ServoStar (Sxxx)/AKD mapped respectively
**AKD mapped ONLY

AKM Feedback Option Motor Connector Availability

Feedback and Connector Availability

AKM1

Feedback Code	Connector Code: C	9	M	P	Y
R-	•		•		•
1-, 2-	•		•		•
C-	•		•	•	•
CA		•			
GP, GR	•				•

AKM2

Feedback Code	Connector Code: B	C	9	G	M	P
R-	•	•		•	•	
1-, 2-	•	•		•	•	
Ex	•	•		•	•	
AA, AB	•	•		•	•	
C-	•	•	•	•	•	•
CA,CB			•			
DA,DB	•	•		•	•	
LA, LB	•	•		•	•	
GA, GB	•			•		
GE, GF			•			
GJ, GK	•			•		

AKM3

Feedback Code	Connector Code: C	9	G	M	P
R-	•		•	•	
1-, 2-	•		•	•	
Ex	•		•	•	
AA, AB	•		•	•	
C-	•	•	•	•	•
CA,CB		•			
DA,DB	•		•	•	
LA, LB	•		•	•	
GA, GB	•		•		
GE, GF		•			
GJ, GK	•		•		

AKM4

Feedback Code	Connector Code: C	9	G	M	P
R-	•		•	•	
1-, 2-	•		•	•	
Ex	•		•	•	
AA, AB	•		•	•	
C-	•	•	•	•	•
CA,CB		•			
DA,DB	•		•	•	
LA, LB	•		•	•	
GA, GB	•		•		
GE, GF		•			
GJ, GK	•		•		

AKM5

Feedback Code	Connector Code: C	9	G
R-	•		•
1-, 2-	•		•
Ex	•		•
AA, AB	•		•
C-	•		•
CA,CB		•	
DA,DB	•		•
LA, LB	•		•
GA, GB	•		•
GE, GF		•	
GJ, GK	•		•

AKM6

Feedback Code	Connector Code: C	9	G
R-	•		•
1-, 2-	•		•
Ex	•		•
AA, AB	•		•
C-	•		•
CA,CB		•	
DA,DB	•		•
LA, LB	•		•
GA, GB	•		•
GE, GF		•	
GJ, GK	•		•

AKM7

Feedback Code	Connector Code: C	G	H*
R-	•	•	•
1-, 2-	•	•	•
Ex	•	•	•
AA, AB	•	•	•
C-	•	•	•
DA,DB	•	•	•
LA, LB	•	•	•
GA, GB	•	•	•
GJ, GK	•	•	•

*AKM74Q Only

AKM8

Feedback Code	Connector Code: H*	T
R-	•	•
1-, 2-	•	•
Ex	•	•
AA, AB	•	•
C-	•	•
DA,DB	•	•
LA, LB	•	•
GA, GB	•	•
GJ, GK	•	•

*AKM82T Only

AKM Feedback Options

AKM Feedback Type Specifications

Kollmorgen Smart Feedback Device, Multi-turn (SFD-M) (CB)

The SFD-M Feedback uses a single motor cable, requiring just one cable between the drive and motor.

The feedback has both power and communication on a single wire pair, reducing overall wiring costs. SFD-M offers 24-bit absolute single-turn resolution, batteryless 16-bit (65,536) multi-turn absolute revolutions and an absolute angular accuracy of +/- 1 arc-min.

In addition, the device includes onboard memory for an electronic motor datasheet which enables device auto-recognition for faster setup and commissioning when paired with any Kollmorgen KED, AKD or AKD2G drive.

Angle Measurement:

Single-Turn Resolution: 2^{24} = 16,777,216 counts per rev
Multi-Turn Absolute Range: 2^{16} = 65,536 absolute revolutions* (batteryless)
Accuracy: < +/- 1 arc-min typical 25° C
< +/- 3 arc-min worst case
Electrical Noise: < 2^{-22} Rev rms at full bandwidth
Bandwidth: > 2 kHz at -3 dB
> 1 kHz at -45° phase lag
Max Continuous Speed: 10,000 RPM
Velocity Ripple: < 1% p-p (typical)
Velocity Noise: < 0.3 RPM rms at full bandwidth

Power Supply:

Input Voltage: 7 V - 12 V accepted (at motor terminals)
Input current maximum: 140 mA DC

Digital Communications:

Baud rate: 2.5 MBaud
Signaling: RS-485 differential using differential Manchester encoding
Update period: New position sample every 51.2 µs
Error detection: 5-bit CRC and running parity check

Environmental:

Feedback Operating Temperature: -40 to 120° C
Humidity: 10% to 90% non-condensing
Vibration Resistance: 30g (294 m/s^2) @ 55-2000 Hz (EN60068-2-6)
Shock Resistance: 100g (981 m/s^2) @ 6 ms (EN60068-2-27)

* When paired with AKD, this is limited to 4096 absolute revolutions (12-bits)

Kollmorgen Smart Feedback Device, Gen 3 (SFD3) (CA)

Kollmorgen's proprietary SFD3 Feedback uses a single motor cable, requiring just one cable between the drive and motor. The feedback has both power and communication on a single wire pair, reducing overall wiring costs. In addition, the device includes onboard memory for an electronic motor datasheet.

Angle Measurement:

Resolution: 2^{24}= 16,777,216 counts per rev
Accuracy: < ± 0.75 arc-sec electrical + sensor error
Size 10 sensor error: ± 15 arc-min net (AKM 1)
Size 15 sensor error: ± 8 arc-min net (AKM 2-4)
Size 21 sensor error: ± 9 arc-min net (AKM 5-8)
Electrical Noise: < 2^{-17} Rev rms at full bandwidth
Bandwidth: > 2000 Hz at -3 dB
> 1000 Hz at -45° phase lag
Max Continuous Speed: 20,000 RPM
Velocity Ripple: < 0.2% p-p electronics only
Size 10 sensor: < 3.0% p-p net (AKM 1)
Size 15 sensor: < 2.0% p-p net (AKM 2-4)
Size 21 sensor: < 2.5% p-p net (AKM 5-6)
Velocity Noise: < 4 RPM rms at full bandwidth

Environmental:

Feedback Operating Temperature: -55 to 155° C
Humidity: 10% to 90% non-condensing

Digital Communications:

Baud Rate: 2.5 MBaud
Signaling: RS-485 differential using differential Manchester encoding
Update Period: Once every 51.2 uSec new position sample
Error Detection: 5 bit CRC and running parity check

Power Supply:

Supply at Drive: 7 to 12 V
Supply at SFD in motor: 7 to 12 V
Nominal Supply Current: 65 mA at 10 V
Worst Case Supply: 110 mA at 10 V
Cable Resistance: Com+, Com- net < 10 Ohm net

AKM Feedback Type Specifications

Kollmorgen Smart Feedback Device (SFD) (C-)

The SFD Feedback communicates with the drive over a four-wire interface. Two wires supply up to +5V power at <150 mA and the second pair is an RS-485 digital communications link. The device includes EEPROM memory to save motor parameters.

Angle Measurement:

Resolution: 2^{24} = 16,777,216 counts per rev
Accuracy: < ± 0.75 arc-min electrical + sensor error
Size 10 sensor: ± 15 arc-min net (AKM 1)
Size 15 sensor ± 8 arc-min net (AKM 2,3,4)
Size 21 sensor ± 9 arc-min net (AKM 5,6,7)
Electrical Noise: < 2^{-17} Rev rms at full bandwidth
Bandwidth: > 2000 Hz at -3 dB
> 1000 Hz at -45° phase lag
Max Continuous Speed: > 20,000 RPM
Velocity Ripple: < 0.2% p-p electronics only
Size 10 sensor < 3.0% p-p net (AKM 1)
Size 15 sensor < 2.0% p-p net (AKM 2-4)
Size 21 sensor < 2.5% p-p net (AKM 5-8)
Velocity Noise: < 4 RPM rms at full bandwidth

Environmental:

Feedback Operating Temperature: -55 to 155° C
Humidity: 10% to 90% non-condensing

Digital Communications:

Baud Rate: 2.5 MBaud
Signaling: RS-485 differential, 8 bit data with odd parity compatible with standard UARTs
Update Period: Once every 51.2 uSec new position sample
Error Detection: 5 bit CRC in addition to parity check
EEPROM Memory: Does a data dump when the unit powers up.

Power Supply:

Supply at Drive: 5.0 V ± 0.25 V (±5%)
Supply at SFD in motor: 4.25 V to 5.25 V
Nominal Supply Current: 120 mA
Worst Case Supply: 150 mA
Cable Resistance: +5V, Rtn: < 3.3 Ohm net


Resolver (Feedback)

Resolver Data	Units	AKM1	AKM2-4	AKM 5-8
		1 Speed	1 Speed	1 Speed
Input Voltage	Vrms (tolerance)	7 (± 10%)	8 (± 5%)	8 (± 5%)
	KHz (tolerance)	10 (± 5%)	8 (± 1%)	8 (± 1%)
Input Current Max.	mA MAX.	30	50	46
Transformation Ratio	± 10%	0.5	0.5	0.5
Null Voltage	mVrms MAX.	50	30	30
Max. Error (pk-pk)	MINS.	30	20	18
Phase Shift	Degrees	-9	0	0
Feedback Operating Temperature	°C	-55° to 155°	-55° to 155°	-55° to 155°
Rotor Inertia Max.	kg-cm^2	0.002	0.046	0.497

Resolver Alignment

With positive DC current into phase W and out of phase V (U floats) the resolver is aligned to electrical ±5 counts. ie. Voltage S1-S3 set to null voltage S2-S4 max in phase with reference (R1-R2).

Resolver Winding Configuration



$E_{R1-R2} = E_{SIN(\omega T)}$
$E_{S1-S3} = KE_{R1-R2\ SIN\Ø}$
$E_{S2-S4} = KE_{R1-R2\ COS\Ø}$

AKM Feedback Options

AKM Feedback Type Specifications

HIPERFACE Options

HIPERFACE DSL® (GE / GF)

Type		Single-Turn "GE"	Multi-Turn "GF"
Frame Size		AKM2-6	AKM 2-6
Resolution per revolution	bits	18	18
Input Voltage	Vdc	7 to 12	7 to 12
Current Consumption	mA MAX.	150	150
Feedback Operating Temperature	°C MIN./MAX.	-20/115	-20/115
Inertia	kg-cm²	0.0045	0.0045
Output Interface		Hiperface DSL	
Manufacturer Product Type		EKS36	EKM36

HIPERFACE Absolute Sin/Cos Encoder (GA / GJ, GB / GK)

Type		Single-Turn "GA/GJ"	Multi-Turn "GB/GK"
Frame Size		AKM2-8	AKM 2-8
Sin/Cos period per revolution	-	128	128
Input Voltage	Vdc	7 to 12	7 to 12
Current Consumption	mA Typical	60	60
Feedback Operating Temperature	°C MIN./MAX.	-20/110	-20/110
Inertia	kg-cm²	0.0045	0.0045
Output Interface		Absolute Hiperface Sin/Cos Encoder	
Manufacturer Product Type		SKS36	SKM36

*GA/GB Feedbacks are "mapped" for ServoStar (Sxxx) Series drives
**GJ/GK Feedbacks are "mapped" for AKD/AKD2G Series drives.

HIPERFACE Capacitive Encoder (GP / GR)

Type		Single-Turn "GP"	Multi-Turn "GR"
Frame Size		AKM1	AKM1
Sin/Cos period per revolution	-	16	16
Input Voltage	Vdc	7 to 12	7 to 12
Current Consumption	mA MAX.	50	50
Feedback Operating Temperature	°C MIN./MAX.	-40/115	-20/115
Inertia	kg-cm²	0.001	0.001
Output Interface		Capacitive Hiperface Encoder	
Manufacturer Product Type		SEK34	SEL34

AKM Feedback Type Specifications

Absolute Digital Encoder Options

EnDat Inductive (LA/LB)

Type		Single-Turn "LA"		Multi-Turn "LB"	
Frame Size		AKM2-3	AKM 4-8	AKM2-3	AKM 4-8
Sin/Cos period per revolution	-	16	32	16	32
Input Voltage	Vdc	4.75 to 10	4.75 to 10	4.75 to 10	4.75 to 10
Current Consumption	mA Typical, at 5V	85 (no load)	85 (no load)	100	102 (no load)
Feedback Operating Temperature	°C MIN./MAX.	-40/115	-20/115	-40/115	-20/115
Inertia	kg-cm^2	0.002	0.021	0.002	0.021
Output Interface		HEIDENHAIN EnDat 2.1/01			
Vibration Resistance – EN 60068-2-6	g [m/s^2]	Stator ≤41 g [400 m/s^2] – Rotor ≤61 g [600 m/s^2] – 55 to 2000 Hz			
Shock Resistance – EN 60068-2-27	g [m/s^2]	≤100 g [981 m/s^2] – 6 ms			
Manufacturer Product Type		ECI1118	ECI1319	EQI1130	EQI1331

Encoder Alignment: With positive DC current into phase W and out of phase V (U floats) the encoder is aligned to ±3 electrical degrees.

EnDat Optical (DA / DB)

Type		Single-Turn "DA"		Multi-Turn "DB"	
Frame Size		AKM2-4	AKM 5-8	AKM2-4	AKM 5-8
Cycles per Revolution (# of abs. revs.)	-	512 (1)	2048 (1)	512 (4096)	2048 (4096)
Input Voltage	Vdc	3.6 to 14	3.6 to 14	3.6 to 14	3.6 to 14
Current Consumption	mA Typical	85 (no load)	85 (no load)	105 (no load)	105 (no load)
Feedback Operating Temperature	°C MIN./MAX.	-40/115	-40/115	-40/115	-40/115
Inertia	kg-cm^2	0.04	0.026	0.04	0.026
Output Interface		HEIDENHAIN EnDat 2.2/01			
Manufacturer Product Type		ECN1113	ECN1313	EQN1125	EQN1325

Encoder Alignment: With positive DC current into phase W and out of phase V (U floats) the encoder is aligned to ±1 electrical degree.

BiSS Optical (AA / AB)

Type		Single-Turn "AA"		Multi-Turn "AB"	
Frame Size		AKM2-4	AKM 5-8	AKM2-4	AKM 5-8
Cycles per Revolution (# of abs. revs.)	-	2048 (1)	2048 (1)	2048 (4096)	2048 (4096)
Input Voltage	Vdc (tolerance)	5 (-5%/+10%)	5 (± 10%)	5 (-5%/+10%)	5 (± 10%)
Current Consumption	mA Typical	100 (without load)	100 (without load)	150 (without load)	100 (without load)
Feedback Operating Temperature	°C MIN./MAX.	-15/120	-15/120	-15/120	-15/120
Inertia	kg-cm^2	0.025	0.038	0.025	0.038
Output Interface		BiSS B			
Manufacturer Product Type		AD34	AD58	AD34	AD58

Encoder Alignment: With positive DC current into phase W and out of phase V (U floats) the encoder is aligned to ±1 electrical degree.


AKM Feedback Options

AKM Feedback Type Specifications


Commutating Encoder Option

Commutating Encoder (2–)

Parameter	Units	1-	2-	ED	EE	EF	EF	EG	EM	EH	EN	EJ
Frame Size		AKM1-8	AKM1-8	AKM2-8	AKM2-8	AKM2-4	AKM5-8	AKM2-8	AKM2-8	AKM2-8	AKM2-8	AKM2-8
Input Voltage	Vdc ±10%	5										
Output Data	–	TTL Differential Line Driver (Sink/Source 20mA MAX.)										
Line Count per revolution	–	1,024	2,048	500	1,000	2,000	2,000	2,500	4,096	5,000	8,192	10,000
Frequency Response	KHz	200							500		1,000	
Max. Speed	RPM	12,000	12,000	12,000	12,000	12,000	7,500	12,000	7,324	8,000	3,662	3,000
Min. Edge Separation of Incremental Channel	°e MIN.	45										
Index to U Comm Channel	–	±1°m Index Center to U Falling Edge										
Index Pulse Width	–	Gated With B Low										
Incremental Channel Accuracy	–	±1 Arc Min. Max. Edge to Edge										
Max. Acceleration	Rad/s²	100,000										
Feedback Operating Temperature	°C	-20 to 120										
Storage Temperature	°C	-25 to 120										




Compliments available on all channels



Max. Misalignment between rising edge of commutation track V & zero crossing of back EMF UV <= 5° electrical.

Motor Connections



Output Comm: Open Collector W 2.2 k OHMS
ExternalL Pull Ups
(SINK 8 mA MAX.)

AKM® Servo Motor Connector Options

Connector Options

Code	Thermal Sensor*	Used with	IP Rating**	Connection type	Description
B	PTC	AKM2	IP65	2 SpeedTec Ready connectors, size 1.0 (M23)	Angled, rotatable, mounted on motor
C	PTC	AKM1-AKM2	IP65	2 SpeedTec Ready connectors, size 1.0 (M23)	On 0.5m cable
C	PTC	AKM3-AKM7	IP65	2 SpeedTec Ready connectors, size 1.0 (M23)	Angled, rotatable, mounted on motor
9	PT1000	AKM1	IP65	1 hybrid itec connector	Rotatable, mounted on motor
9	PT1000	AKM2-AKM6	IP65	1 SpeedTec Ready connector, size 1.0 (M23)	Angled, rotatable, mounted on motor
G	PTC	AKM2-AKM7	IP67	2 SpeedTec Ready connectors, size 1.0 (M23)	Straight, mounted on motor
H	PTC	AKM7 & AKM82T	IP65	1 feedback threaded connector, size 1.0 (M23) 1 power threaded connector, size 1.5 (M40)	Angled, rotatable, mounted on motor
M	PTC	AKM1-AKM4	IP20	2 Molex connectors, $I_C < 6$ A	On 0.5m cable
P	PTC	AKM1-AKM4	IP20	1 Molex connector, $I_C < 6$ A	On 0.5m cable
T	PTC	AKM8	IP65	1 terminal box for power 1 feedback threaded connector, size 1.0 (M23)	Mounted on motor
Y	PTC	AKM1	IP65	1 ytec connector	Rotatable, mounted on motor

NOTE: These connector options are only valid for the "00" or "01" Customization/Seal Option variants. Stainless Steel Hummel connectors are used for AKM Washdown (0W) and AKM Food Grade (0F) variants.

*For Thermal Device Curves, reference see the Thermal Sensor Protective Devices page.
**IP ratings shown apply ONLY to the connector and the connector base/bushing on motor.

Feedback and Connector Availability

AKM1

Feedback Code \ Connector Code	C	9	M	P	Y
R-	•		•		•
1-, 2-	•		•		•
C-	•		•	•	•
CA		•			
GP, GR	•				•

AKM2

Feedback Code \ Connector Code	B	C	D	9	G	M	P
R-	•	•			•	•	
1-, 2-	•	•			•	•	
Ex	•	•			•	•	
AA, AB	•	•			•	•	
C-	•	•	•		•	•	•
CA,CB				•			
DA,DB	•	•			•	•	
LA, LB	•	•			•	•	
GA, GB	•				•		
GE, GF				•			
GJ, GK	•				•		

AKM3-4

Feedback Code \ Connector Code	C	D	9	G	M	P
R-	•			•	•	
1-, 2-	•			•	•	
Ex	•			•	•	
AA, AB	•			•	•	
C-	•	•		•	•	•
CA,CB			•			
DA,DB	•			•	•	
LA, LB	•			•	•	
GA, GB	•			•		
GE, GF			•			
GJ, GK	•			•		

AKM5-6

Feedback Code \ Connector Code	C	9	G
R-	•		•
1-, 2-	•		•
Ex	•		•
AA, AB	•		•
C-	•		•
CA,CB		•	
DA,DB	•		•
LA, LB	•		•
GA, GB	•		•
GE, GF		•	
GJ, GK	•		•

AKM7

Feedback Code \ Connector Code	C	G	H*
R-	•	•	•
1-, 2-	•	•	•
Ex	•	•	•
AA, AB	•	•	•
C-	•	•	•
DA,DB	•	•	•
LA, LB	•	•	•
GA, GB	•	•	•
GJ, GK	•	•	•

*AKM74Q Only

AKM8


Feedback Code \ Connector Code	H*	T
R-	•	•
1-, 2-	•	•
Ex	•	•
AA, AB	•	•
C-	•	•
DA,DB	•	•
LA, LB	•	•
GA, GB	•	•
GJ, GK	•	•

*AKM82T Only

AKM® Servo Motor Connector Pinouts


Dual Cable Options – Power & Feedback

B, C, G, H, & T Power Connector Pinouts




C- Connectors (AKM1 & AKM2 Only)

Connector Part Number: BKUA-199-NN-00-11-0200-000



B- Connectors (AKM2 Only)
C- Connectors (AKM3-7)


Connector Part Number: BEDC-110-NN-00-00-1216-000



G- Connectors (AKM2 - AKM7)

Connector Part Number:
BEGA-120-NN-00-00-0200-000

B-, C- & G- Power Connector Pinout




Pin	Function
1	U
‡	PE
3	W
4	V
A	Brake +
B	Brake -
C	N/C
D	N/C

H- Connector Pinout

(AKM7 & AKM82T Only)


Connector Part Number:
CEDE-270-NN-00-00-0051-000




H- Connectors

T- Connector


(AKM8 Only)





Pin	Function
U	U
‡	PE
W	W
V	V
+	Brake +
-	Brake -

Power Connector (View Facing Front)




Clamp	Function
U	U
PE	PE
W	W
V	V
B+	Brake +
B-	Brake -


Note: The connector part numbers given are only valid for the "00" and "01" customization/seal option variants. For mating connector selection, please work with TE Connectivity to select the proper option based on your cable design (cable diameter and conductor size). Pinout still valid for AKM Washdown "0W" and AKM Food Grade "0F" Stainless Steel Hummel connector variants.

Dual Cable Options – Power & Feedback


B, C, G, H, & T Feedback Connector Pinouts



C- Connectors (AKM1 & AKM2 Only)



B- Connectors (AKM2 Only)
C- Connectors (AKM3-7)




G- Connectors (AKM2 - AKM7)

Connector Part Number:

AKUA-012-NN-00-09-0200-000
(For AKM1 & 2, "C- Connector")

AEDC-110-NN-00-00-1215-000
(For AKM2 "B- Connector", AKM3-7, "C- Connector" and AKM7 & AKM8 "H- Connector")

AEGA-110-NN-00-00-0201-000
(For AKM2-7 "G- Connector")




SFD2

Pin	Function
1	SFD +5V
2	SFD +5V RTN
3	SFD COM-
4	SFD COM+
5	SFD COM Shield (AKM 1, 2)
6	N/C
7	N/C
8	N/C
9	N/C
10	N/C
11	N/C
12	N/C

Resolver

Pin	Function
1	N/C
2	Thermal Sensor +
3	S4 COS –
4	S3 SIN –
5	R2 REF –
6	Thermal Sensor –
7	S2 COS +
8	S1 SIN +
9	R1 REF +
10	N/C
11	N/C
12	N/C



Connector Part Number:

AKUA-015-NN-00-09-0200-000
(For AKM1 & 2, "C- Connector")

AEDC-139-NN-00-00-1215-000
(For AKM2 "B- Connector", AKM3-7, "C- Connector" and AKM7 & AKM8 "H- Connector")

AEGA-139-NN-00-00-0201-000
(For AKM2-7 "G- Connector")

Commutating Encoder

Pin	Function
1	B
2	$\overline{B}$
3	A
4	$\overline{A}$
5	Z
6	$\overline{Z}$
7	GND
8	Thermal Sensor +
9	Thermal Sensor –
10	Vcc
11	N/C
12	N/C
13	N/C
14	N/C
15	U
16	V
17	W


EnDat®/BiSS


Pin	Function
1	B –
2	GND
3	A –
4	Vcc
5	DATA
6	N/C
7	Thermal Sensor +
8	Clock
9	B +
10	Un Sense (Common)
11	A +
12	Up Sense (VCC)
13	$\overline{DATA}$
14	Thermal Sensor –
15	$\overline{Clock}$
16	N/C
17	N/C

HIPERFACE®Analog

Pin	Function
1	SIN +
2	GND
3	COS +
4	Vcc
5	Data
6	N/C
7	Thermal Sensor +
8	N/C
9	REF SIN
10	N/C
11	REF COS
12	N/C
13	$\overline{Data}$
14	Thermal Sensor –
15	N/C
16	N/C
17	N/C

H- Connectors
(AKM74Q - AKM82T Only)






T- Connector
(AKM8 Only)

Note: The connector part numbers given are only valid for the "00" and "01" customization/seal option variants. For mating connector selection, please work with TE Connectivity to select the proper option based on your cable design (cable diameter and conductor size). Pinout still valid for AKM Washdown "0W" and AKM Food Grade "0F" Stainless Steel Hummel connector variants.


AKM® Servo Motor Connector Pinouts

Dual Cable Options – Power & Feedback

ytec®- Y- Connector Pinout – AKM1 only



Feedback Power + Brake



ytec- Connector

Power Connector


Pin	Function
1	BR+
2	BR-
3	N/C
4	N/C
5/E	N/C
A	Phase U
B	Phase W
C	Phase V
⏚	PE


Connector Part Number: See Options for Commutating Encoder or SFD2/Resolver/ HIPERFACE

Commutating Encoder

Pin	Function
1	B
2	$\overline{B}$
3	A
4	$\overline{A}$
5	Z
6	$\overline{Z}$
7	GND
8	Thermal Sensor +
9	Thermal Sensor –
10	Vcc
11	N/C
12	N/C
A	U
B	V
C	W

Connector Part Number: EEDA-103-NN-00-00-0001-000





SFD2

Pin	Function
1	SFD +5 V
2	SFD +5 V RTN
3	SFD COM-
4	SFD COM+
5	N/C
6	N/C
7	N/C
8	N/C
9	N/C
10	N/C
11	N/C
12	N/C

Resolver

Pin	Function
1	N/C
2	Thermal Sensor +
3	S4 COS –
4	S3 SIN –
5	R2 REF –
6	Thermal Sensor –
7	S2 COS +
8	S1 SIN +
9	R1 REF +
10	N/C
11	N/C
12	N/C

HIPERFACE® Analog

Pin	Function
1	Thermal Sensor +
2	Thermal Sensor –
3	N/C
4	REF SIN
5	REF COS
6	Data +
7	Data –
8	SIN +
9	COS +
10	Vcc
11	GND
12	N/C


Connector Part Number: EEDA-101-NN-00-00-0001-000

Note: The connector part numbers given are only valid for the “00” and “01” customization/seal option variants. For mating connector selection, please work with TE Connectivity to select the proper option based on your cable design (cable diameter and conductor size). Pinout still valid for AKM Washdown “0W” and AKM Food Grade “0F” Stainless Steel Hummel connector variants.

Hybrid Single Cable Options – Power & Feedback

9-, and E Hybrid Connector Pinouts

9- Connector Pinout – Hybrid combined power and SFD3, SFD-M, and HDSL feedback



Power + SFD2 /SFD3 / DSL


Power + SFD3/SFD-M/DSL

Pin	Function
1	U
⏚	PE
3	W
4	V
A	Brake +
B	Brake –
C	SFD – / DSL –
D	SFD + / DSL +

Power + SFD2


Pin	Function
1	U
⏚	PE
3	W
4	V
A	SFD +5 V
B	SFD +5 V RTN
C	SFD COM –
D	SFD COM +

Connector Part Number:
BEDC-110-NN-00-00-1216-000



D- Connector

itec®- 9- Connector Pinout – AKM1 only



Power + SFD3


Power + SFD3

Pin	Function
1	Brake +
2	Brake –
3	SFD –
4	SFD +
5/E	N/C
A	Phase U
B	Phase W
C	Phase V
⏚	PE

Power + SFD2


Pin	Function
1	SFD +5 V
2	SFD +5 V RTN
3	SFD COM –
4	SFD COM+
5/E	N/C
A	Phase U
B	Phase W
C	Phase V
⏚	PE

Connector Part Number:
EEDA-201-NN-00-00-0800-000




itec- Connector

E- Connector Pinout – AKM7-8 only



Power + SFD3

Pin	Function
U	U
⏚	PE
W	W
V	V
+	Brake +
-	Brake -
1	SFD–
2	SFD+



E- Connector

Note: The connector part numbers given are only valid for the “00” and “01” customization/seal option variants. For mating connector selection, please work with TE Connectivity to select the proper option based on your cable design (cable diameter and conductor size). Pinout still valid for AKM Washdown “0W” and AKM Food Grade “0F” Stainless Steel Hummel connector variants.


AKM® Servo Motor Connector Pinouts

Dual Molex Cable Options – Power & Feedback

"M" Power and Feedback Connector Options

(AKM 1, 2, 3 & 4 Only) If additional dimensions or connectors are required, contact Kollmorgen Customer Support.

"M" Power Connector Options



Power Connector – No Brake


Pin	Function	Color
1	U	Blue
2	V	Brown
3	W	Violet
4	Gnd	Grn/Yel
5	Shield	

Shield Connected to Motor
Ground Internal to Motor

Power Connector – Brake

Pin	Function	Color
1	U	Blue
2	V	Brown
3	W	Violet
4	Gnd	Grn/Yel
5	Shield	
6	Brake+	Black
7	Brake-	Black
8	N/C	

Shield Connected to Motor
Ground Internal to Motor




"M" Feedback Connector Options

SFD

Pin	Function	Color
1	SFD +5V	Red
2	SFD +5V RTN	Black
3	SFD COM-	Yellow
4	SFD COM+	Blue
5	SFD COM Shield	
6	N/C	
7	N/C	
8	N/C	
9	N/C	
10	N/C	

Shield is Not Connected at Motor End



Resolver


Pin	Function	Color
1	N/C	
2	Thermal Sensor +	Orange
3	S4, COS-	Blue
4	S3, SIN-	Black
5	R2, REF-	Blk/Wht
6	Thermal Sensor –	Orange/White
7	S2, COS+	Yellow
8	S1, SIN+	Red
9	R1, REF+	Red/Wht
10	Shield	

Shield is Not Connected at Motor End

Commutating Encoder

Pin	Function	Color
1	B	Green
2	$\overline{B}$	Grn/Blk
3	A	Blue
4	$\overline{A}$	Blue/Blk
5	Z	Violet
6	$\overline{Z}$	Violet/Blk
7	Gnd	Black
8	Thermal Sensor +	Orange
9	Thermal Sensor –	Orange/White
10	Vcc	Red
11	N/C	
12	N/C	
13	N/C	
14	N/C	
15	U	Brown
16	V	Grey
17	W	White
18	Shield	

Shield is Not Connected at Motor End



Absolute Encoder

Pin	"AA" & "AB"	DA, DB & LA, LB	Color
1	B-	B-	Red/Blk
2	Gnd	Gnd	Wht/Grn
3	A-	A-	Yel/Blk
4	Vcc (5Vdc)	Vcc (5Vdc)	Brn/Grn
5	Data	Data	Gray
6	N/C	N/C	
7	Thermal Sensor+	Thermal Sensor+	Green
8	Clock	Clock	Violet
9	B+	B+	Blu/Blk
10	Un Sense (Common)	Un Sense (Common)	White
11	A+	A+	Grn/Blk
12	Up Sense (VCC)	Up Sense (VCC)	Blue
13	$\overline{Data}$	$\overline{Data}$	Pink
14	Thermal Sensor-	Thermal Sensor-	Brown
15	$\overline{Clock}$	$\overline{Clock}$	Yellow
16	N/C	N/C	
17	N/C	N/C	
18	N/C	Shield	

Shield is Not Connected at Motor End

Hybrid Molex Cable Options – Power & Feedback

"P" Power + SFD Connector Option


(AKM 1, 2, 3 & 4 Only - Not available for Brake Motors)

Power + SFD

Pin	Function	Color
1	SFD +5V	Red
‡	SFD +5V RTN	Black
3	Power Shield	
4	Ground	Grn/Yel
5	U	Blue
6	SFD COM-	Yellow
7	SFD COM+	Blue
8	SFD COM Shield	
9	V	Brown
10	W	Violet

Power Shield Connected to Motor Ground Internal to Motor

Feedback Shield is Not Connected at Motor End



Molex® Connector-Cable Lookup Table

(AKM 1, 2, 3 & 4 Only)




Molex® Cable Mating Connectors


Cable Function	Connector Option Code	Motor Cable Connector	Motor Cable Composition	Mating Connector
Power	M	Molex 39-01-4056 (Eng No. 5559-05P3)	5-Pin Power Conector - No Brake	Molex 39-01-4050
		Molex 39-01-3083 (Eng No. 5559-08P1)	8-pin Power Connector with Brake	Molex 39-01-2080
Feedback		Molex 43020-1001	8-Pin SFD	Molex 43025-1000
		Molex 43020-1001	8-Pin Resolver	Molex 43025-1000
		Molex 43020-1801	18-Pin Commutating Encoder	Molex 43025-1800
		Molex 43020-1801	18-Pin Absolute Encoder DA, DB, LA, LB	Molex 43025-1800
		Molex 43020-1801	18-Pin Absolute Encoder AA, AB	Molex 43025-1800
Power + SFD	P	Molex 39-01-3103 (Eng No. 5559-10P1)	10-Pin Power + SFD - No Brake	Molex 39-01-2100

I. L10 Bearing Fatigue


AKM1 MOTORS
20,000 HOURS L_{10} BEARING LIFE



AKM2 MOTORS
20,000 HOURS L_{10} BEARING LIFE




AKM3 MOTORS
20,000 HOURS L_{10} BEARING LIFE




AKM4 MOTORS

20,000 HOURS L_{10} BEARING LIFE




AKM5 MOTORS

20,000 HOURS L_{10} BEARING LIFE




AKM6 MOTORS

20,000 HOURS L_{10} BEARING LIFE




I. L10 Bearing Fatigue (Continued)


AKM7 MOTORS
20,000 HOURS L_{10} BEARING LIFE



AKM8 MOTORS
20,000 HOURS L_{10} BEARING LIFE



AKM83 & 84 MOTOR WITH REINFORCED BEARING
20,000 HOURS L_{10} BEARING LIFE



II. Shaft Loading

Motor	Max. Radial Force (N)	Max. Axial Force (N)
AKM1	48	200
AKM2	150	600
AKM3	340	600
AKM4	500	1400
AKM5	830	1740
AKM6	1940	2200
AKM7	2300	3000
AKM8	2752	4750

The maximum radial load ratings reflect the following assumptions:

1. Motors are operated with peak torque of the longest member of the frame size.
2. Fully reversed load applied to the end of the smallest diameter standard mounting shaft extension. Excluding AKM4X-EK which is rated at 240 N max. radial force.
3. Infinite life with 99% reliability.
4. Safety factor = 2.

III. Teflon Shaft Seals

There is a normal break-in period for our Teflon® shaft seals. Best conditions during the break-in period would be at the operational temperature and speed that would be typical for the application.

During the break-in period, some "shedding" of Teflon material is normal. The debris is not a sign of seal deterioration or failure. The material "shed" should be reduced with usage.

Typically, a few hours at operational speed is enough to break-in the shaft seal.

IV. Thermal Sensor Protective Devices

The standard version of each motor is fitted with an electrically isolated PTC Avalanche-Type thermal sensor or PT1000 RTD Linear thermal sensor, depending on connector (see the Connector Options table). The thermal sensors do not provide any protection against short, heavy overloading.

The motor can be delivered with a PT1000 or KTY84/130 equivalent sensor optionally for certain connectors (see Thermal Sensor options 1 and 2). Please consult Kollmorgen Customer Support for optional thermal device requests based on motor configuration.


With digital feedback systems SFD (C), SFD3 (CA), SFD-M (CB) and Hiperface DSL (GE/GF), the temperature sensor status is transmitted digitally and evaluated in the drive.

Provided that our configured feedback cables are used, the sensor is integrated into the monitoring system of the digital servo amplifiers.


Thermal Device Options: Resistance vs. Temperature Graphs

Kollmorgen AKD drives can directly interpret information from the motor thermal sensors to properly reflect the motor winding temperature. For other drives please refer to the graph Delta Between Motor Winding and Thermal Device on the following page.


Standard



Option 1



Option 2



Note 1: PTC thermistor (155°C ± 5°C switching temperature) installed.

Resistance at 25°C: ≤550 ohms.


Switching Resistance: ≥1330 ohms within ±5°C of switch temperature.

Note 2: Optional KTY84-130 Nominal Resistance at 25°C, 603 ohms.

V. Delta Between Motor Winding and Thermal Device

When using a drive other than the Kollmorgen AKD you will need to account for the difference (Delta) in temperature between the value reported by the thermal sensor and the actual motor winding temperature. This is necessary to insure proper operation and protection of the motor.
The provided graph shows the delta between the reported device temperature on the x axis and the motor winding temperature on the y axis and should be used to adjust the response of the system for the difference between the thermal sensors reported temperature and the actual motor winding temperature.

Examples:
At 60°C on thermal device temperature the winding temperature will be 1.8°C higher (61.8°C).
At 130°C on thermal device temperature the winding temperature will be 8.1°C higher (138.1°C).





VI. Motor Phasing Diagram

When the motor is rotated clockwise (CW) as viewed from front shaft end, the following BEMF voltage waveforms result:

» Voltage phase-UV leads Voltage phase-VW by 120-degrees
» Voltage phase-VW leads Voltage phase-WU by 120-degrees
» Voltage phase-WU leads Voltage phase-UV by 120-degrees

BEMF Waveforms





Complete Motion and Automation Solutions

The highest performance and the right fit for any application.



AUTOMATION FOR AGVs & MOBILE ROBOTS

Control Panel • Vehicle Control • Navigation • Robotics

ACCESSORIES

Cables & Connectors • Shielding Solutions
Brake Resistors • Chokes & Filters


Learn more about our products.

Online Design Tools




Product Selector

Quickly choose the ideal products for your application needs.



Motioneering®

Size your motion system based on application requirements and motion profiles.



Performance Curve Generator

Optimize housed and frameless motor windings based on power and environmental factors.



3D Models

Visualize products in 3D and download CAD files for use in your design.



Stepper Optimizer

Interactively choose the most efficient stepper solution for your application.



AKD2G Safe Dynamic Brake Calculator

Specify and size the right braking components while saving development time.

Learn more and try our design tools now.

More Expertise for a More Successful Machine

Our global engineering, service and support network provides deep knowledge of all the major industries that rely on advanced motion control and automation technology. We offer world-class engineering expertise, self-service design tools, personalized field service, and easy access to our design, application and manufacturing centers in strategic locations across the globe.

About Kollmorgen

Kollmorgen, a Regal Rexnord brand, has more than 100 years of motion experience, proven in the industry's highest-performing, most reliable motors, drives, linear actuators, AGV (Automated Guided Vehicle) control solutions, and automation control platforms. We deliver breakthrough solutions that combine exceptional performance, reliability and ease of use, giving machine builders an irrefutable marketplace advantage.

KOLLMORGEN

A REGAL REXNORD BRAND

www.kollmorgen.com

Specifications are subject to change without notice. It is the responsibility of the product user to determine the suitability of this product for a specific application. All trademarks are the property of their respective owners

© 2025 Kollmorgen Corporation. All rights reserved

KM_SG_000077_RevF_EN